



# Technical Bulletin

**PHENOMENAL BRANDS, Phenopatch Products**  
A division of DAP Products Inc.  
2400 Boston Street, Suite 200, Baltimore, Maryland 21224  
Phone: 410-675-2100 or 800-543-3840

Revised: 12/15/2016

## DAP® Phenopatch® Spackling Paste

- Ready to use
- Interior use

**Packaging:** 1/2 pint tub (236 mL), 1 quart tub (946 mL), 1 gallon tub (3.78L)  
**Color:** White  
**UPC Numbers:** 7079810222, 7079810224, 7079876859

### Company Identification:

**Manufacturer:** PHENOMENAL BRANDS, Phenopatch Products, A division of DAP Products Inc.,  
2400 Boston Street, Baltimore, Maryland 21224

**Usage Information:** 410-779-3265

**Order Information:** 410-779-3265

Also, visit the Phenopatch website at [www.phenopatch.com](http://www.phenopatch.com).

### Product Description:

DAP® Phenopatch® Spackling Paste is a ready mixed, easy-to-use patching material used to fill holes and cracks and treat surfaces prior to painting. The product has a smooth working consistency, dries quickly, is non-shrinking and sands easily. Recommended for interior use only.

### Suggested Uses:

Ideal for filling and concealing small cracks, nail holes and blemishes in:

- Drywall

### Surface Preparation & Application:

- Surface must be clean, dry and free of dust and particles.
- Use sandpaper to dull glossy surfaces before repairing.
- Stir thoroughly before use. Apply with a clean putty knife.
- For a smoother finish, dip putty knife in water and lightly smooth spackling.
- For repairs deeper than 1/8", apply two or more layers allowing to dry between applications.
- Spackling Paste can be sanded or painted 1-5 hours after application, depending on temperature, humidity and depth of fill. Wet sanding is recommended to avoid generation of dust.
- Clean tools immediately with water.

### **Typical Physical & Chemical Characteristics:**

Consistency:	Paste
Vehicle:	latex polymer
Volatile:	Water
Filler:	Inert filler
Odor:	Mild
Weight/Gallon:	15.4
Solids:	75%
Application Temperature:	50°F Minimum
Service Temperature:	0°F to 150°F
Shelf Life:	1 Year
Freezing:	Freeze/Thaw stable 5 cycles
Drying Time:	1 to 5 hours depending on temperature, relative humidity and depth of fill.
Painting:	Takes either oil or latex-base paint.
SDS No.:	00079944005

### **Clean Up:**

Wash tools immediately after use with water. Be sure container is closed and tightly sealed. Store in a cool, dry place.

### **Safety:**

See product label and Safety Data Sheet (SDS) for safety information. For an SDS, contact PHENOMENAL BRANDS at 410-779-3265 or visit [www.phenopatch.com](http://www.phenopatch.com).

### **Warranty:**

If product fails to perform as directed, within one year from the date of purchase, call 410-779-3265, with your sales receipt and product container available, for replacement product or sales price refund. PHENOMENAL BRANDS will not be responsible for incidental or consequential damages.