

MINWAX® Technical Data Sheet
MINWAX® WOOD FINISH STAIN MARKER

DESCRIPTION:

Minwax Wood Finish Stain Markers contain Minwax Wood Finish oil-based stain in a convenient marker form. The Stain Markers are available in eight colors: Golden Oak, Provincial, Red Oak, Red Mahogany, Early American, Cherry, Dark Walnut, and Pickled Oak.

RECOMMENDED USE:

Designed for touchups and repair of furniture, cabinets, doors and floors. Minwax Wood Finish Stain Markers offer a fast, convenient, no-mess application for staining small hobby and woodcraft projects as well as for detailing wood or other decorative wood techniques.

APPLICATION NOTES:

- 1) Shake marker well.
- 2) Remove cap and depress tip gently a few times on scrap paper or wood to start stain flowing. Approve color match before applying to main project.
- 3) Apply stain to wood. NOTE: Stain must penetrate into the wood to be effective. The Wood Finish Stain Markers will not dry and cure properly when used on a finish.
- 4) Wipe off excess stain with cloth if needed.
- 5) Replace cap tightly after use.
- 6) Allow 4 – 6 hours for stain to dry.

Read all label directions and cautions carefully before use.

DRY TIME:

Allow 4 – 6 hours for stain to dry. Dry time may be extended due to high humidity, low temperatures, or inadequate ventilation.

CLEANUP/STORAGE:

Use mineral spirits or paint thinner. Replace cap tightly after use. Store pen on side. Do not use or store near heat, sparks, flame or other source of ignition. **KEEP OUT OF REACH OF CHILDREN.** If tip dries out or hardened after extended use, remove tip and soak in mineral spirits overnight.

SAFETY:

Read all label directions and cautions carefully before use.

CAUTION! Combustible. Contains mineral spirits. Harmful or fatal if swallowed. If swallowed, do not induce vomiting. Do not take internally. Skin irritant. Avoid contact with skin and eyes. Combustible. Do not use or store near heat, sparks, flame or other source of ignition. When using do not smoke. Use only with adequate ventilation. Close container after each use. Contact a physician for more health information. **KEEP OUT OF REACH OF CHILDREN.**

MINWAX® Technical Data Sheet
MINWAX® WOOD FINISH STAIN MARKER

PHYSICAL PROPERTIES:

Resin type:	Thixotropic Soya Alkyd	Testing method:
Solvent:	Mineral spirits or Paint Thinner	ASTM D-4236
Odor:	Mild hydrocarbon	
Luster (@60):	Low	
No. of coats:	Two	
Dry-time:	12 Hours	
Flash point:	106 Fahrenheit	SETAFLASH*
VOC	4.6 lbs./gal. (550 g/l)	
Coverage (sq. ft./gal.):	200 sq. ft / qt.	
% Solids:	40.02 – 41.94	
Specific gravity:	0.806 – 0.853	
Viscosity (centipose):	4,000 – 10,000 Centipoise	

*Closed cup; SETAFLASH is a registered trademark of Stanhope-Seta Limited.