



21-215 W I FLAT WHITE NOW SPRAY PAINT

MSDS Number

BZCHH

National Stock Number

8010-00F047102

Product Name

21-215 W I FLAT WHITE NOW SPRAY PAINT

Manufacturer

KRYLON DIV OF SHERWIN WILLIAMS

Product Identification

Product ID:21-215 W I FLAT WHITE NOW SPRAY PAINT

MSDS Date:05/01/1992

FSC:8010

NIIN:00F047102

MSDS Number: BZCHH

Responsible Party

KRYLON DIV OF SHERWIN WILLIAMS

31500 SOLON RD

SOLON , OH 44139-3908

US

Emergency Phone: 216-292-7400/800-832-2541

Info Phone: 216-292-7400/800-832-2541

Cage: KRYLO

Contractor

KRYLON DIV OF SHERWIN WILLIAMS

SOLON, OH 44139-3908

US

216-292-7400/800-832-2541

Cage: KRYLO

Ingredients

XYLENE, DIMETHYLBENZENE, XYLOL (IARC - GROUP 3) *96-1*

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 9%

OSHA PEL100 PPM

ACGIH TLV: 100 PPM, SKIN

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ACETONE; DIMETHYL KETONE; 2-PROPANONE

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 36-37%



OSHA PEL2400 MG/CUM

ACGIH TLV: 750 PPM

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

TALC (POWDER), (ASBESTOS FREE), TALCUM; HYDROUS MAGNESIUM

CAS: 14807-96-6

RTECS: WW2710000

Fraction By Weight: 4.32%

OSHA PEL2 MG/CUM (RESP DUST)

ACGIH TLV: 2 MG/CUM (RESP DUST)

TITANIUM DIOXIDE, TIO2 (SUSPECTED ANIMAL CARCINOGEN, IARC

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 4%

OSHA PEL15 MG/CUM

ACGIH TLV: 10 MG/CUM (DUST)

86%/WT

RTECS: 9999999VO

PROPANE (DIMETHYLMETHANE) *96-1*

CAS: 74-98-6

RTECS: TX2275000

Fraction By Weight: 14%

OSHA PEL1000 PPM

ACGIH TLV: SIMPLE ASPHYXIAN

ISOBUTANE, 2-METHYLPROPANE

CAS: 75-28-5

RTECS: TZ4300000

Fraction By Weight: 14%

OSHA PEL1800 MG/CUM

ACGIH TLV: 1000 PPM

TOLUENE (IARC CARC- GROUP 3) *96-1*

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 11%

OSHA PEL100 PPM



ACGIH TLV: 100 PPM

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ETHYL BENZENE *96-1*

CAS: 100-41-4

RTECS: DA0700000

Fraction By Weight: 1.86%

OSHA PEL435 MG/CUM

ACGIH TLV: 434 MG/CUM

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:MAY CAUSE IRRITATION OF EYES, SKIN & RESPIRATORY SYSTEM & NERVOUS SYSTEM DEPRESSION. EXTREME OVEREXPOSURE MAY RESULT IN POSSIBLY DEATH. PROLONGED OVEREXPOSURE TO SOLVENTS MAY CAUSE ADVERSE EFFECTS TO THE LIVER, URINARY, BLOOD-FORMING CARDIOVASCULAR & REPRODUCTIVE SYSTEMS. (SEE SUPP)
Explanation of Carcinogenicity:NONE
Effects of Overexposure:IRRITATION, UNCONSCIOUSNESS, HEADACHE, DIZZINESS, NAUSEA, LOSS OF COORDINATION, REDNESS, ITCHING, BURNING SENSATION

First Aid

First Aid:INHALATION: REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM & QUIET. SKIN: WASH AREA THOROUGHLY W/SOAP & WATER. EYES: FLUSH W/LARGE AMOUNTS OF WATER FOR 15 MINS. OBTAIN MEDICAL ATTENTION IN ALL CAS ES.

Fire Fighting

Flash Point Method:PMCC
Flash Point:Lower Limits:1
Upper Limits:12.8
Extinguishing Media:CO2, DRY CHEMICAL, FOAM
Fire Fighting Procedures:WEAR FULL PROTECTIVE EQUIPMENT W/SCBA. WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE PREFERRED. WATER MAY BE USED TO COOL CLOSED CONTAINERS.
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE DUE TO THE BUILDUP OF PRESSURE WHEN EXPOSED TO EXTREME HEAT. VAPORS WILL ACCUMULATE READILY & MAY IGNITE EXPLOSIVELY.

Accidental Release

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. VENTILATE & REMOVE W/INERT ABSORBENT.

Handling

Handling and Storage Precautions:KEEP FROM IGNITION SOURCES. DON'T PUNCTURE/INCINERATE/EXPOSE TO TEMP >120F. USE APPROVED BONDING & GROUNDING PROCEDURES. KEEP OUT OF REACH OF CHILDREN
Other Precautions:DURING USE & UNTIL ALL VAPORS ARE GONE, KEEP AREA VENTILATED, DON'T SMOKE, EXTINGUISH FLAME/IGNITION SOURCE. DON'T TAKE INTERNALLY. AVOID BREATHING VAPOR & SPRAY MIST. AVOID CONTACT W/SKIN & EYES.

Exposure Controls

Respiratory Protection:IF EXPOSURE CAN'T BE CONTROLLED LIMITS BY VENTILATION, WEAR A PROPERLY FITTED ORGANIC VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH/MSHA. WHEN



SANDING/ABRADING THE DRIED FILM, WEAR A DUST /MIST RESPIRATOR
NIOSH/MSHA APPROVED.
Ventilation:LOCAL EXHAUST: PREFERRED. GENERAL EXHAUST: ACCEPTABLE IF
EXPOSURE IS MAINTAINED Protective Gloves:REQUIRED
Eye Protection:REQUIRED
Other Protective Equipment:SAFETY SPECTACLES W/UNPERFORATED
SIDESHIELDS.
Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:Vapor Density:>1
Evaporation Rate & Reference:FASTER THAN ETHER

Stability

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME, ELECTRICAL
EQUIPMENT, TEMPS >120F, SUNLIGHT/OTHER IGNITION SOURCES.
Hazardous Decomposition Products:BY FIRE: CO₂, CO

Disposal

Waste Disposal Methods:WASTE MUST BE TESTED FOR IGNITABILITY TO
DETERMINE THE APPLICABLE EPA HAZARDOUS WASTE NUMBERS. DON'T
INCINERATE. DEPRESSURIZE CONTAINER. DISPOSE OF IAW/LOCAL, STATE &
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.