



## SPRAY MATCH SOLVENT BASED COATING

#16-3395, #C16-3395, #16-4395, #C16-4395, K16-4395

A specialized blend of solvents and propellant which can be used to aerosolize most enamel, lacquer, vinyl, and acrylic paints. The unique cap functions as the paint reservoir during the filling process. There is no prep or cleanup work involved. To be used exclusively with the Z-2500, Z-2501 and Z-2507 Fill One Machines.

### Suggested Uses:

Aerosolize custom matched colors  
Quickly touch up damaged areas  
Automotive touch up  
Maintenance and industrial  
OEM applications

### Benefits:

Individual cans can be aerosolized  
Special colors  
No brushes or rollers to clean up  
Low odor  
Reduced overspray

### Packaging:

UPC Code	
Cans per case	12
Shipping weight per case	13.6 lbs.
Container	16 fluid ounce can
Label weight	8 ounces
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

### Properties:

Flammability	Extremely Flammable
Flash point	-19F
Specific Gravity	0.69
MIR value	0.74
HAPs content	0%
Storage Temperature	40-100F
Application Temperature	50-90F
Shelf life Unfilled:	Guaranteed for 2 years

### Dry Time:

Not Applicable until modified

### Gloss:

Not applicable until modified

**Filled cans should be used as soon as possible.**

### Available Colors:

While Seymour of Sycamore has tested paints from many different manufacturers, compatibility with the **Solvent Blend** aerosols can not be guaranteed. Additional label information and/or warnings may be required if the injected product's safety information varies from that of the **Solvent Blend**. Filling aerosol cans is a manufacturing process, and the manufacturer is ultimately responsible for complying with hazardous labeling standards.