



# SAFETY DATA SHEET

Revision date 08-Jan-2019

Version 23

Supersedes Date: 19-Apr-2018

## Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### Product identifier

**Product Code** 140.0003004

**Product Name** WOOD TONED D&S STAIN HEARTWOOD

### Other means of identification

No information available

### Recommended use of the chemical and restrictions on use

Paint, Coatings

### Details of the supplier of the safety data sheet

*See section 16 for more information*

The Valspar Corporation  
PO Box 1461  
Minneapolis, MN 55440

**E-mail address** [msds@valspar.com](mailto:msds@valspar.com)

### Emergency telephone number

United States of America 1-888-345-5732

## Section 2: HAZARDS IDENTIFICATION

### Classification

Skin corrosion/irritation	Category 2
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 2
Reproductive toxicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable liquids	Category 3

### Label elements



Signal word

**DANGER**

#### HAZARD STATEMENTS

Flammable liquid and vapor  
Causes skin irritation  
May cause an allergic skin reaction  
May cause genetic defects  
Suspected of causing cancer  
May damage fertility or the unborn child  
May cause drowsiness or dizziness  
May be fatal if swallowed and enters airways

#### PREVENTION

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Wash face, hands and any exposed skin thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace. Use only outdoors or in a well-ventilated area. P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

#### RESPONSE

IF exposed or concerned: Get medical advice/attention.

##### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

##### Skin

If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

##### Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

##### Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

##### Fire

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction.

#### STORAGE

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool.

#### DISPOSAL

Dispose of contents/containers in accordance with local regulations.

#### HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)

No information available.

#### OTHER HAZARDS

spontaneously combustible material. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal.

#### UNKNOWN ACUTE TOXICITY

.0001% of the mixture consists of ingredient(s) of unknown toxicity.

### Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	weight-%
Petroleum distillates, hydrotreated light	64742-47-8	50 - 70
Folpet	133-07-3	0.3 - 1
Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester	10605-21-7	0.1 - 0.3
Zirconium ethyl hexoate	22464-99-9	0.1 - 0.3
2-Butanone, oxime	96-29-7	0.1 - 0.3
Ethylbenzene	100-41-4	0.1 - 0.3

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

## Section 4: FIRST AID MEASURES

### First Aid Measures

#### **General advice**

IF exposed or concerned: Get medical advice/attention.

#### **Eye contact**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

#### **Skin Contact**

If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

#### **Inhalation**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

#### **Ingestion**

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

### Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

### Indication of any immediate medical attention and special treatment needed

**Note to physicians** Treat symptomatically.

## Section 5: FIRE FIGHTING MEASURES

### Suitable extinguishing media

Dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam.

Not to be used for safety reasons: Strong water jet

### Specific hazards arising from the chemical

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by skin contact. spontaneously combustible material. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal. Keep product and empty container away from heat and sources of ignition.

### Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

## Section 6: ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

#### **Personal precautions**

Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Take precautionary measures against static discharges.

#### **For emergency responders**

Use personal protection recommended in Section 8.

#### **Environmental precautions**

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

#### **Methods and material for containment and cleaning up**

##### **Methods for containment**

Prevent further leakage or spillage if safe to do so.

##### **Methods for cleaning up**

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. Take up mechanically, placing in appropriate containers for disposal.

## **Section 7: HANDLING AND STORAGE**

#### **Precautions for safe handling**

##### **Advice on safe handling**

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal.

##### **General Hygiene Considerations**

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing.

#### **Conditions for safe storage, including any incompatibilities**

##### **Storage Conditions**

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place. Keep tightly closed in a dry and cool place.

##### **Incompatible materials**

Strong oxidizing agents.

## **Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### **Control parameters**

##### **Exposure Limits**

If S\* appears in the OEL table, it indicates this chemical contains a skin notation.

<b>Chemical Name</b>	<b>ACGIH TLV</b>	<b>OSHA PEL</b>	<b>NIOSH IDLH</b>
Zirconium ethyl hexoate 22464-99-9	STEL: 10 mg/m <sup>3</sup> Zr TWA: 5 mg/m <sup>3</sup> Zr	TWA: 5 mg/m <sup>3</sup> Zr	IDLH: 25 mg/m <sup>3</sup> Zr TWA: 5 mg/m <sup>3</sup> except Zirconium tetrachloride Zr STEL: 10 mg/m <sup>3</sup> Zr
Ethylbenzene	TWA: 20 ppm	TWA: 100 ppm	IDLH: 800 ppm

100-41-4		TWA: 435 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>
----------	--	----------------------------	--

**Appropriate engineering controls**

**Engineering Controls**

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Tight sealing safety goggles.

**Skin and body protection**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear suitable protective clothing. Personnel should wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber.

**Hand Protection**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

**Respiratory protection**

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

**Thermal Protection**

No information available

**Section 9: PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

<b>Physical state</b>	liquid
<b>Appearance</b>	No information available
<b>Odor</b>	Solvent
<b>Color</b>	clear
<b>Odor Threshold</b>	No information available
<b>pH value</b>	No information available
<b>Melting point/freezing point</b>	No information available
<b>Boiling point / boiling range</b>	No information available °C / °F
<b>flash point</b>	40 °C / 104 °F
<b>evaporation rate</b>	No information available
<b>Flammability (solid, gas)</b>	No information available
<b>Flammability Limit in Air</b>	
<b>Upper flammability limit:</b>	No information available
<b>Lower flammability limit:</b>	No information available
<b>Vapor Pressure</b>	No information available
<b>vapor density</b>	No information available
<b>Density (lbs per US gallon)</b>	7.25
<b>specific gravity</b>	No information available
<b>Solubility(ies)</b>	No information available
<b>Partition coefficient</b>	No information available
<b>Autoignition temperature</b>	No information available
<b>Decomposition temperature</b>	No information available
<b>Kinematic viscosity</b>	No information available
<b>Dynamic viscosity</b>	No information available

**Other information**

## Section 10: STABILITY AND REACTIVITY

<b>Reactivity</b>	No information available.
<b>Chemical stability</b>	Stable under normal conditions.
<b>Possibility of Hazardous Reactions</b>	None under normal processing.
<b>Hazardous polymerization</b>	None under normal processing.
<b>Conditions to avoid</b>	Heat, flames and sparks.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous Decomposition Products</b>	Carbon monoxide. Carbon dioxide (CO <sub>2</sub> ).

## Section 11: TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

#### **Eye contact**

Not applicable

#### **Skin Contact**

Causes skin irritation

May cause an allergic skin reaction

#### **Ingestion**

May be fatal if swallowed and enters airways

#### **Inhalation**

May cause drowsiness or dizziness

### Numerical measures of toxicity - Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum distillates, hydrotreated light 64742-47-8	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 5.2 mg/L ( Rat ) 4 h
Folpet 133-07-3	= 2636 mg/kg ( Rat )	> 22600 mg/kg ( Rabbit ) > 5000 mg/kg ( Rat )	> 5 g/m <sup>3</sup> ( Rat ) 2 h > 0.48 g/m <sup>3</sup> ( Rat ) 4 h
Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester 10605-21-7	= 6400 mg/kg ( Rat ) > 5050 mg/kg ( Rat )	= 2 g/kg ( Rat ) = 8500 mg/kg ( Rabbit )	-
Zirconium ethyl hexoate 22464-99-9	-	-	-
2-Butanone, oxime 96-29-7	= 930 mg/kg ( Rat )	1000 - 1800 mg/kg ( Rabbit )	> 4800 mg/m <sup>3</sup> ( Rat ) 4 h
Ethylbenzene 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.4 mg/L ( Rat ) 4 h

### Numerical measures of toxicity - Product Information

**UNKNOWN ACUTE TOXICITY** .0001% of the mixture consists of ingredient(s) of unknown toxicity.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### **Carcinogenicity**

According to IARC, Volume 93, no significant exposure to primary particles of carbon black is thought to occur from use in paints since the pigment is bound to other materials.

Chemical Name	ACGIH	IARC	NTP	OSHA
Ethylbenzene 100-41-4	A3	Group 2B		X

*ACGIH (American Conference of Governmental Industrial Hygienists)*



ICAO/IATA SP A112); Limited Quantity (49 CFR 173.150(b), ICAO Part 3 Chapter 4, IATA 2.7, IMDG Chapter 3.4); Viscous Liquid (49 CFR 173.121(b), IMDG 2.3.2.2, IATA 3.3.3.1.1, ICAO 3.2.2, ADR 2.2.3.1.5); Does Not Sustain Combustion (49 CFR 173.120(a), IATA 3.3.1.3, ICAO 3.1.3, IMDG 2.3.1.3, ADR 2.2.3.1.1 Note 1); or others as allowed under hazardous materials/dangerous goods regulations.

## Section 15: REGULATORY INFORMATION

### International Inventories

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

All components are listed or exempt from listing.

**DSL** - Canadian Domestic Substances List

Not all components are listed or exempt from listing

### US Federal Regulations

Chemical Name	SARA 313 - Threshold Values %	Metals	Hazardous air pollutants (HAPs) content
Ethylbenzene 100-41-4 0.1 - 0.3	0.1		Present

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Ethylbenzene 100-41-4	1000 lb	X	X	X

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester 10605-21-7	10 lb		RQ 10 lb final RQ RQ 4.54 kg final RQ
Ethylbenzene 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

### US State Regulations

#### **Rule 66 status of product**

Not photochemically reactive.

#### **California Proposition 65**

WARNING: This product contains chemicals known to the State of California to cause cancer.

#### **U.S. EPA Label information**

**EPA Pesticide registration number** Not applicable

#### **U.S. State Right-to-Know Regulations**

Chemical Name
Petroleum distillates, hydrotreated light 64742-47-8
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Paraffin waxes and Hydrocarbon waxes 8002-74-2
Folpet 133-07-3
Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester 10605-21-7
Zirconium ethyl hexoate 22464-99-9
2-Butanone, oxime 96-29-7
Ethylbenzene

**Section 16: OTHER INFORMATION****HMIS****Health hazards** 3\*

\* = Chronic Health Hazard

**Flammability** 2**Physical hazards** 0**Personal Protection** X**Supplier Address**

Valspar Consumer Headquarters 8725 W. Higgins Rd. Suite 1000 Chicago, IL 60631 773-628-5500	The Valspar Corporation 4999 36th St. Grand Rapids, MI 49512 800-253-3957	Valspar Plasti-Kote 1636 Shawson Dr. Mississauga, Ontario L4W 1N7 905-671-8333
--	--	---

**Prepared By** Product Stewardship**Revision date** 08-Jan-2019**Revision Note** No information available**Disclaimer**

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. **UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.**

**End of Safety Data Sheet**