



Preserva Wood® Solid Tint Base



PRODUCT DATA SHEET

Product Description

Preserva Wood® Solid Color Oil Stain is formulated with organic oils and an alkyd resin to make it tough, durable and natural. Our Solid Stain is a true oil based stain that offers maximum hide and superior protection for all exterior wood surfaces.

Surfaces to Stain

- New or existing exterior wood (smooth and rough)
- Fences
- Decks and railings
- Wood siding
- Log homes
- Shake or shingles

Coverage

Smooth wood

400-500 square feet
per gallon

Rough Wood

250-350 square feet
per gallon

Technical Information

Base: Alkyd resin

Solvent: Mineral Spirits

Dry time: 24-48 hours depending on temperature and humidity.

% Solids by weight 61-63%

Weight 8.6-9.1 lbs/gal

Bases: Neutral and Deep

Pigment Organic/Inorganic
TiO₂

VOC less than 250 g/l

Warranty

If you are not completely satisfied with the performance of this product when applied to a properly prepared surface according to label directions, manufacturer will replace the product or refund the purchase price at the manufacturer's option. Proof of purchase required, photograph and complaint description.

Surface Preparation

Proper surface preparation is essential to assure maximum performance. Preserva Wood® must be able to penetrate into the wood. All previous coatings should be removed in order to ensure proper penetration and adhesion of the new stain. Previously painted or sealed surfaces must be stripped and/or sanded. Loose wood fibers should be removed by sanding and then washing the wood surface. Wood must be clean and dry before staining. Persistent black spots which appear when wood is wet are mold and mildew. Use an approved product to kill and remove all mildew prior to staining.

Mix

Stir stain well and stir often during use, making sure all pigment has been well mixed before using.

Test

Test stain for penetration and appearance before staining.





Preserva Wood® Solid Tint Base



PRODUCT DATA SHEET

Application

Be sure the weather will be dry for at least 24 hours before and after applying the stain. Your wood should be clean and dry before staining. Do not apply over previously stained or sealed surfaces. Apply to cool dry wood when the temperature is between 50 and 90 degrees F. Do not apply in the heat of the day. Apply using a stain pad, natural bristle brush, or professional spray equipment. Natural bristle brushes made for applying oil based stains work best. When spraying, back brush to ensure even penetration and color uniformity. Treat the full length of each board, keeping a wet edge to avoid lap marks. Over application may result in a shiny surface, sagging, or poor drying. Allow 24-48 hours dry time, depending on temperature and humidity. **FOR WOOD SUBSTRATES ONLY!** Place oil soaked rags, clothing and other application materials in water immediately after use.

Cleanup and Disposal

Soak oily rags, clothes, or any other material in a water filled sealed container to avoid spontaneous combustion (fire). After one week, wring out and lay flat to air dry outdoors, away from wood, paper or any combustible material. Do not throw away until completely dry. Tools and equipment should be cleaned with paint thinner. Seal partial containers tightly when not in use. Store in a cool, dry place with no source of ignition. Dispose of empty cans in accordance with local, state and federal laws.

Warning

Rags, steel wool, or waste soaked with Preserva Wood® may spontaneously catch fire if improperly discarded. Immediately after each use, place rags, steel wool, and waste in a sealed, water filled metal container.

Maintenance

Clean all exterior wood with a mild detergent based cleaner. Small touch-ups are possible however all prep work must be performed prior to re-application on a large scale.

Lead Warning

WARNING! If you scrape, sand or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should avoid exposure. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log onto

www.epa.gov/lead

Contact Us

1-800-797-2537

info@preservaproducts.com

Preserva Products, Ltd.

12860 Earhart Avenue

Auburn, CA 95602

