



SAFETY DATA SHEET

Issue Date 26-Mar-2013

Revision Date 23-Apr-2013

Version 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

Product Name PC CRETE EPOXY PUTTY

Other Means of Identification

SDS # 130415

Recommended Use of the Chemical and Restrictions on Use

Recommended Use Sealants and adhesives.

Details of the Supplier of the Safety Data Sheet

Supplier Address

Protective Coatings Co.
221 S Third St.
Allentown, PA 18102 USA

Emergency Telephone Number

Company Phone Number 610-432-3543 / 800-220-2103
Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Classification

| | |
|-----------------------------------|------------|
| Skin Corrosion/Irritation | Category 2 |
| Serious Eye Damage/Eye Irritation | Category 2 |
| Skin sensitization | Category 1 |

Signal Word

Warning

Hazard Statements

Causes skin irritation
Causes serious eye irritation
May cause an allergic skin reaction



Appearance Off-white paste

Physical State Solid

Odor Pungent Strong

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
 Wear protective gloves/protective clothing/eye protection/face protection
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Contaminated work clothing should not be allowed out of the workplace

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 Immediately call a POISON CENTER or doctor/physician
 IF ON SKIN: Wash with plenty of soap and water
 Take off contaminated clothing and wash it before reuse
 Get immediate medical advice/attention

Other Hazards

Harmful to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS No | Weight-% |
|---------------------------------------|------------|----------|
| Bisphenol A - Epichlorohydrin polymer | 25068-38-6 | 10-30 |
| Titanium dioxide | 13463-67-7 | 1-5 |
| Crystalline silica | 14808-60-7 | 0.1-1 |

4. FIRST AID MEASURES

First Aid Measures

| | |
|-----------------------|--|
| General Advice | Provide this SDS to medical personnel for treatment. |
| Eye Contact | Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. |
| Skin Contact | Wash contaminated skin with soap and water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse. |
| Inhalation | Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |

Ingestion

Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most Important Symptoms and Effects, both Acute and Delayed**Symptoms**

Causes skin irritation. May include redness, drying and cracking of skin. Causes eye irritation. Exposed individuals may experience eye tearing, redness and discomfort. Irritating to mouth, throat and stomach.

Indication of any Immediate Medical Attention and Special Treatment Needed**Note to Physicians**

Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media None known.

Specific Hazards Arising from the Chemical

No specific fire or explosion hazard.

Hazardous Combustion Products Carbon oxides. Oxides of sulfur. Halogenated compounds. Metal oxide/oxides.

Protective Equipment and Precautions for Firefighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures**Personal Precautions**

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For Emergency Responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "Personal Precautions" in this section.

Environmental Precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and Material for Containment and Cleaning Up**Methods for Containment**

Prevent further leakage or spillage if safe to do so. Move containers from spill area.

Methods for Cleaning Up

Keep in suitable, closed containers for disposal. For waste disposal, see section 13 of the SDS.

7. HANDLING AND STORAGE

Precautions for Safe Handling**Advice on Safe Handling**

Handle in accordance with good industrial hygiene and safety practice. Use personal protection recommended in Section 8. Wash face, hands, and any exposed skin thoroughly after handling. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Avoid contact with skin, eyes or clothing. Empty containers retain product residue and can be hazardous. Do not eat, drink or smoke when handling this product. Remove contaminated clothing and shoes. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace.

Conditions for Safe Storage, Including any Incompatibilities**Storage Conditions**

Keep containers tightly closed in a dry, cool and well-ventilated place. Store in accordance with local regulations. Protect from direct sunlight. Do not store in unlabeled or mislabeled containers.

Packaging Materials

Keep in original container.

Incompatible Materials

None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|----------------------------------|--|---|---|
| Titanium dioxide 13463-67-7 | TWA: 10 mg/m ³ | TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust | IDLH: 5000 mg/m ³ |
| Crystalline silica 14808-60-7 | TWA: 0.025 mg/m ³ respirable fraction | (vacated) TWA: 0.1 mg/m ³ respirable dust : (30)/(%SiO ₂ + 2) mg/m ³ TWA total dust : (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction | IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust |

Other Information

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Appropriate Engineering Controls**Engineering Controls**

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits. Ensure that eyewash stations and safety showers are close to the workstation location.

Individual Protection Measures, such as Personal Protective Equipment

| | |
|---------------------------------------|--|
| Eye/Face Protection | Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. |
| Skin and Body Protection | <p>Hand protection: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated</p> <p>Body protection: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product</p> <p>Other skin protection: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</p> |
| Respiratory Protection | Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. |
| General Hygiene Considerations | Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. |

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

| | | | |
|-------------------------------------|---------------------------------------|-------------------------|----------------|
| Physical State | Solid | Odor | Pungent Strong |
| Appearance | Off-white paste | Odor Threshold | Not available |
| Color | Off-white | | |
| Property | Values | Remarks • Method | |
| pH | Not applicable | | |
| Melting Point/Freezing Point | Not available | | |
| Boiling Point/Boiling Range | Not available | | |
| Flash Point | > 93.3 °C / > 199.9 °F | Setaflash | |
| Evaporation Rate | Not available | | |
| Flammability (Solid, Gas) | Not available | | |
| Upper Flammability Limits | Not available | | |
| Lower Flammability Limit | Not available | | |
| Vapor Pressure | Not available | | |
| Vapor Density | Not available | | |
| Relative Density (Specific Gravity) | Not determined | | |
| Water Solubility | 0 g/L; Insoluble in cold or hot water | | |
| Solubility in Other Solvents | Not determined | | |
| Partition Coefficient | Not determined | | |
| Autoignition Temperature | Not available | | |
| Decomposition Temperature | >150°C (>302°F) | | |
| Kinematic Viscosity | Not available | | |
| Dynamic Viscosity | Not available | | |
| Explosive Properties | Not determined | | |
| Oxidizing Properties | Not determined | | |
| Density | Relative Density 2.03 | | |

10. STABILITY AND REACTIVITY

Reactivity

No specific test data related to reactivity available for this product or its ingredients.

Chemical Stability

The product is stable.

Possibility of Hazardous Reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to Avoid

Keep out of reach of children.

Incompatible Materials

None known based on information supplied.

Hazardous Decomposition Products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Product Information

| | |
|---------------------|--|
| Eye Contact | Causes serious eye irritation. |
| Skin Contact | Causes skin irritation. |
| Inhalation | Under normal conditions of intended use, this material is not expected to be an inhalation hazard. |
| Ingestion | Irritating to mouth, throat and stomach. |

Component Information

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|---|-----------------------|----------------------|-----------------|
| Bisphenol A - Epichlorohydrin polymer 25068-38-6 | = 11400 mg/kg (Rat) | 20000 mg/kg (rabbit) | - |
| Titanium dioxide 13463-67-7 | > 10000 mg/kg (Rat) | - | - |
| Crystalline silica 14808-60-7 | = 500 mg/kg (Rat) | - | - |

Information on Physical, Chemical and Toxicological Effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

Sensitization May cause an allergic skin reaction.

Carcinogenicity Titanium dioxide is a possible carcinogen when it appears as a respirable dust. Crystalline Silica is considered to be a human carcinogen when in respirable form (dust / powder).

| Chemical Name | ACGIH | IARC | NTP | OSHA |
|---------------|-------|------|-----|------|
|---------------|-------|------|-----|------|

| | | | | |
|----------------------------------|----|----------|-------|---|
| Titanium dioxide 13463-67-7 | | Group 2B | | X |
| Crystalline silica 14808-60-7 | A2 | Group 1 | Known | X |

ACGIH (American Conference of Governmental Industrial Hygienists)
 A2 - Suspected Human Carcinogen
 IARC (International Agency for Research on Cancer)
 Group 1 - Carcinogenic to Humans
 Group 2B - Possibly Carcinogenic to Humans
 NTP (National Toxicology Program)
 Known - Known Carcinogen
 OSHA (Occupational Safety and Health Administration of the US Department of Labor)
 X - Present

Numerical Measures of Toxicity

Not determined

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects

Persistence and Degradability

Not determined

Bioaccumulation

Not determined

Mobility

Not determined

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

14. TRANSPORT INFORMATION

| | |
|-------------|---|
| Note | Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances. |
| DOT | Not regulated |
| IATA | Not regulated |
| IMDG | Not regulated |

15. REGULATORY INFORMATION

International Inventories

| | |
|--------------|---------------------------------------|
| TSCA | Listed |
| ENCS | Not determined |
| IECSC | All components are listed or exempted |
| KECL | Not determined |
| PICCS | Not determined |
| AICS | Not determined |

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 311/312 Hazard Categories

| | |
|--|-----|
| Acute health hazard | Yes |
| Chronic Health Hazard | No |
| Fire hazard | No |
| Sudden release of pressure hazard | No |
| Reactive Hazard | No |

SARA 313

Not determined

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

| Chemical Name | California Proposition 65 |
|---------------------------------|---------------------------|
| Titanium dioxide - 13463-67-7 | Carcinogen |
| Crystalline silica - 14808-60-7 | Carcinogen |

U.S. State Right-to-Know Regulations

| Chemical Name | New Jersey | Massachusetts | Pennsylvania |
|----------------------------------|------------|---------------|--------------|
| Titanium dioxide 13463-67-7 | X | X | X |
| Crystalline silica 14808-60-7 | X | X | X |

16. OTHER INFORMATION

| | | | | |
|-------------|-----------------------|---------------------|-------------------------|----------------------------|
| NFPA | Health Hazards | Flammability | Instability | Special Hazards |
| | 2 | 1 | 0 | Not determined |
| HMIS | Health Hazards | Flammability | Physical Hazards | Personal Protection |
| | 1 | 1 | 0 | Not determined |

Issue Date 26-Mar-2013
Revision Date 23-Apr-2013
Revision Note New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet