



CRAFTSMEN QUALITY STAINS AND FINISHES SINCE 1953.

TECHNICAL DATA SHEET

OLD MASTERS® TUNG OIL VARNISH

AVAILABLE SIZES: Pint (08), Quart (04) and Gallon (01)

PRODUCT CODES: 50508 Pint

50504 Quart

50501 Gallon

PRODUCT DESCRIPTION: Old Masters® Tung Oil Varnish creates a beautiful, hand-rubbed finish on previously stained or bare wood. This product is a superior quality finish made from a blend of Tung oil and fine varnishes. It dries to a durable, non-oily finish which is water and alcohol resistant. It penetrates the wood surface to protect fine furniture, enhancing the natural beauty and richness of the woodgrain.

SURFACE PREPARATION: All surfaces must be clean, dry and free from dirt, wax, grease, glue and other contaminants.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION:

1. Apply Old Masters® Tung Oil Varnish with a lint-free cloth, rubbing in the direction of the woodgrain. For brushing applications, brush in the direction of the woodgrain.
2. Wipe off excess with a clean, lint-free cloth.
3. Allow the surface to dry 4 to 6 hours.
4. Buff lightly with fine steel wool and remove dust prior to recoating.
5. Reapply. Subsequent coats of Tung Oil Varnish will increase the depth and luster of the finish.

THINNING: Do not thin. Use as packaged.

CLEAN UP: Using a cleaning solvent, such as paint thinner or mineral spirits, is recommended for cleanup. The use of paint thinners or mineral spirits may violate VOC compliancy in your area. Check with your local government agencies to ensure proper compliancy.

To avoid spontaneous combustion during temporary storage, soak soiled rags and waste immediately after use in a water-filled, closed metal container.

MAX VOC: 450 g/L (3.76 lb/gal)



CRAFTSMEN QUALITY STAINS AND FINISHES SINCE 1953.

TECHNICAL DATA SHEET

OLD MASTERS® TUNG OIL VARNISH

TECHNICAL DATA

GLOSS:	90 @ 60° on a non-porous surface	WEIGHT PER GALLON:	7.1 - 7.2 LBS
SOLIDS BY WEIGHT:	47-48%	FLASH POINT:	102 °F
SOLIDS BY VOLUME:	42-43%	VISCOSITY AT 77 °:	25-30S #2 Ford
V.O.C.:	450 grams/liter	AVERAGE DRY TIME @ 70°F AND 50% R.H.:	Approximately 4-6 hours
THEORETICAL COVERAGE @ Mil DFT:	678 sq. ft.	VEHICLE:	Oil/varnish
COVERAGE @ RECOMMENDED DFT	Not applicable	RECOMMENDED THINNER:	Do not thin. Used as packaged.
RECOMMENDED DFT PER COAT:	.5 - 1.0 mil		

Limited Warranty Since Old Masters® does not control the application of its products, nor is the condition of the surface to which they are applied, a Limited Warranty provided. If the products do not perform as specified, for whatever reason, Old Masters® liability will under no circumstances exceed the replacement of the product.