

LIQUID NAILS® BRAND

FUZE*IT®

HYBRID TECHNOLOGY BONDS ALMOST EVERYTHING

ALL SURFACE

LN-2000

Interior/Exterior

A new standard for super premium construction adhesives featuring hybrid technology that bonds nearly everything to everything. Offers instant grab and can be applied to dry and damp surfaces.

PRODUCT DESCRIPTION

LIQUID NAILS® FUZE*IT® All Surface construction adhesive, LN-2000, is formulated with a proprietary hybrid-polymer blend for best-in-class adhesion. It bonds everything to everything (except polyethylene and polypropylene) and it bonds in any weather condition. Hot, cold, wet or dry, FUZE*IT All Surface offers a durable, flexible bond that is two times stronger than fasteners alone. Certified by UL Environment to meet the GREENGUARD GOLD Standard as a low emitting material.

RECOMMENDED FOR

Use on nearly all surfaces, porous or non-porous, wet or dry, including:

- Glass
- Metal
- Ceramic
- Granite
- Mirrors*
- Wood
- Marble
- Rubber
- Laminate
- Tile
- Anything else except polyethylene and polypropylene

**Note: Use in conjunction with permanent mechanical fasteners when hanging mirrors*

NOT RECOMMENDED FOR

- Polyethylene
- Polypropylene
- Teflon, EPDM & TPO

PRODUCT ADVANTAGES

- Hybrid technology bonds almost everything
- Bonds in harsh weather conditions
- Bonds wet or dry surfaces
- Interior & exterior
- Two times stronger than fasteners alone
- Low VOC and very low odor – VOC compliant
- Comes with a detachable nozzle for easy cleaning for reuse
- Excellent water-resistance
- Exceeds ASTM C-557



HARSH
WEATHER



2X
STRONGER
VS
FASTENERS
ALONE



INSTANT
GRAB



INTERIOR
EXTERIOR



LOW VOC
LOW ODOR

Please research all installation instructions and read entire label and Material Safety Data Sheet for safety, health & environmental information prior to use. See other cautions on last page.





FUZE*IT[®]

HYBRID TECHNOLOGY BONDS ALMOST EVERYTHING

LN-2000

Interior/Exterior

ALL SURFACE

APPLYING THE PRODUCT

Surfaces must be clean and free of loose particles. Can be used on damp or wet surfaces. For faster set time on dry surfaces, wipe surfaces lightly with a damp cloth prior to applying adhesive. For better adhesion, surfaces that are very smooth may be lightly sanded. Unscrew nozzle, cut tip of cartridge, replace nozzle and cut to required bead size. Insert into cartridge gun. Apply 1/4" (6 mm) wide bead of adhesive to one surface. Press surfaces together within 10 minutes. Clamp, tape, or brace parts together if necessary until adhesive has set, typically 4 to 6 hours for porous surfaces.

CLEAN UP

Remove excess material with dry cloth when wet, scraping and mineral spirits when dry.

DISPOSAL

Place **empty** containers in normal refuse for disposal. Remove residual product from the container, allow product to dry, and dispose of in conjunction with normal household waste. Contact your sanitation department or household hazardous waste coordinator for information concerning possible re-use of unused caulks and sealants.

EAD-C8

LIMITED WARRANTY

PPG warrants satisfaction with this product when handled and applied according to label instructions. If product is not as warranted, PPG will, at your option, furnish replacement product or refund the purchase price. Please call 1-800-634-0015 for details. This limited warranty excludes labor or the cost of labor and is given as the exclusive warranty and remedy. **No warranty of merchantability, fitness for purpose or other warranty, express or implied, is made. PPG shall not be liable for any special, incidental or consequential damages.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above exclusions/limitations may not apply. This limited warranty gives specific legal rights; you may have other rights that vary by state.

WARNING! HARMFUL IF SWALLOWED. CAUSES EYE IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness. Do not swallow. Do not get on skin or clothing. Avoid contact with eyes. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. **FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. In case of contact, immediately flush skin with plenty of water while removing contaminated clothing and shoes. Get medical attention if irritation develops. If inhaled, remove to fresh air. If experiencing respiratory symptoms call a POISON CENTER or doctor/physician. Contains: limestone (1317-65-3); proprietary trade secret organic (not available); proprietary silyl terminated polyether (not available); proprietary amide wax (not available); n-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3). Keep out of the reach of children. For workplace use, an MSDS is available from your retailer or by calling (412) 492-5555. **EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.).**

LN-2000

TECHNICAL INFORMATION

Base: Hybrid

Color: Gray

Appearance: Smooth paste

Application Temperature: 0°F to 140°F
(-17°C to 60°C)

Service Temperature: -40°F to 300°F
(-40°C to 149°C)

Sag (ASTM D 2202): <0.10"

Shear Strength: 24 hours—400psi (full strength)

Gallon Weight: 12.2 lbs. (5.53 kg)

Viscosity: 500,000 cps

Open Time: 20 minutes at room temperature

Minimum Cure Time: 24 hours at
room temperature

Freeze Thaw Stability: No effect after 5 cycles

Flammability: Non-flammable

Percent Volatile: < 3%

Coverage: Using full round 1/4" (.64 cm) bead;
28 oz. (858 ml) covers 88 lineal feet
(27 lineal meters)

Shelf Life: One year from date of purchase

Odor: Slight

Specifications: Exceeds ASTM C-557

VOC: < 3% by weight. (< 50 g/L)