



Product Data Sheet MINWAX® Premium Design Series Wood Effects

CHARACTERISTICS:

Premium Design Series products expand the wood finishing market with new on-trend looks, finishes and special effects that today's users want- all in quick and easy formulas that invite them to take on more projects all the time. The **Minwax Premium Design Series Wood Effect** is a water based products that works with wood's tannins to produce a naturally aged look in minutes. Every piece of wood reacts differently, so every product is unique. **Minwax Premium Design Series Wood Effects** is ideal for unfinished wood furniture, cabinets, doors, trim and molding.

Color:	Clear with slight tones of gray or black
Coverage:	275 sq. ft./qt
Drying Time:	
To Touch:	30 minutes
To Sand:	N/A
Recoat:	1 hour
Dry to use/service:	2-4 hours

D04A00001 Weathered Gray

Flash Point:	N.A.
VOC (less exempt solvents):	0
Volume Solids:	0.3%
Weight Solids:	0.4%
Weight per Gallon:	8.3 lb.

D04B00001 Charred Black

Flash Point:	N.A.
VOC (less exempt solvents):	0
Volume Solids:	2.5%
Weight Solids:	1.6%
Weight per Gallon:	8.4 lb.

RECOMMENDED USE:

Interior Use Only; Not for use on floors

SPECIFICATION:

Preferred application systems:

Speed & Clarity

1st: Sanded, bare wood

2nd: Minwax Premium Design Series Wood Effects

3rd (optional): Minwax Polycrylic Ultra Flat sheen

SURFACE PREPARATION:

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at **1-800-424-LEAD** (in US) or contact your local health authority.

Rev: xx/xx/20xx

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative or visit www.paintdocs.com to obtain the most current version of the PDS and/or an SDS.



Product Data Sheet MINWAX® Premium Design Series Wood Effects

Wood must be dry and cleaned of dirt, grease, wax, polish and marks. Old finishes in poor condition should be completely removed and the surface treated as a new surface. Recognize that any surface preparation short of total removal of the old coating may compromise the service length of the system.

For best results, start with a medium grit sandpaper, and increase the grit as you go, finishing with 220 grit paper as final sand. Remove sanding dust with a vacuum or tack cloth.

Do not use steel wool for abrading when using Minwax Premium Design Series Wood Effects. Since steel wool and water can cause rust, steel wool should be avoided around all water- based wood finishing products.

Protect surrounding items with drop cloths, masking tape, etc.

APPLICATION:

Be sure the temperature is above 50°F, and the humidity is below 85%.

Test before applying on a hidden spot to make sure you like the effect.

Product reacts differently with every piece of wood. Preferred wood species: Oak

Stir product well before and occasionally during application. Do not shake or thin product.

Brush	Use a synthetic or foam brush. Brush out evenly in direction of the grain. <u>No wiping required.</u>
--------------	---

Apply in the direction of the grain. No wiping required.

After applying Premium Design Series Wood Effects, let dry for 30-60 minutes.

For a rustic look that will continue to patina with time, topcoat not recommended. For increased durability and protection while maintaining a rustic look, use Minwax Polycrylic in Ultra Flat sheen.

CLEANUP INFORMATION:

Clean spills, spatters, hands and tools immediately after use with soap and warm water.

CAUTIONS:

For interior use only.

Not for use on commercial floors.

Not for use on surfaces continuously wet or under water.

Before using carefully read CAUTIONS on label.