



SUREGRIP® 122 HEAVY DUTY CLEAR STRIPPABLE WALLCOVERING ADHESIVE

DESCRIPTION AND USES

Rust-Oleum® SureGrip® 122 Heavy Duty Clear Strippable Wallcovering Adhesive is a general purpose, ready-to-use for hanging all types of standard wallcoverings from lightweight non-pasted and pre-pasted wallpaper to heavyweight vinyl (up to 34 oz. commercial grade types to include I, II and III). SureGrip 122 flows easily through pasting machines, has strong wet tack and can be easily removed from fabric backed vinyl wallcovering from primed or bare drywall without damage to the surface.

SureGrip 122 is not recommended for hanging borders or wallcoverings over existing vinyl wallcovering without the use of a primer. See "Existing Vinyl Wallcovering" under Application in next column for recommendations. SureGrip 122 is not recommended for hanging foil, Mylar®, flexible wood surfaces (paneling) or un-backed cork. This product is not recommended for hanging non-woven wallcovering if dry removal is desired.

PERFORMANCE CHARACTERISTICS

- For use with standard light to heavyweight non-pasted and pre-pasted wallcoverings
- Strong wet tack and excellent slip for easy positioning
- Provides excellent adhesion
- Spreads and flows easily – Ideal for pasting machines
- Dries clear
- Non-staining, easy clean-up

PRODUCTS

SKU	DESCRIPTION
69384	1-Quart
02881	1-Gallon
2880	5-Gallons

PRODUCT APPLICATION

SURFACE PREPARATION

Surfaces must be clean, dry, sound and free of dust, grease, wax, oil, old wallcovering adhesive, mold and mildew and other residue. Inspect the surface for paint bonding, loose wallcoverings, damaged wallboard or plaster. Remove old or loose wallcovering and residual wallcovering adhesive with DIF® Wallpaper Stripper. Repair unsound surfaces. Seal loose paint or damaged drywall and cured skim coats with Gardz® High Performance Sealer as needed.

PRIMING

Prime all surfaces (including oil-based paints, oil-based primers or oil-based stain-kill coatings) with ShieldZ® Universal, ShieldZ® Universal Plus or ShieldZ Clear Acrylic Wall Size or ShieldZ Oil-Base Wallcovering Primer.

PRODUCT APPLICATION (cont.)

SURFACE PREPARATION (cont.)

MOLD & MILDEW

Eliminate pre-existing mold and mildew by washing the affected area with a solution of ¼ cup of bleach to 1 gallon of water. Wear protection to prevent skin and eye contact. Quickly wash off any solution that comes in contact with your skin. Do not add ammonia or other cleaning agents to the bleach solution. Rinse surface with clean water. Allow surface to dry thoroughly before applying wallcovering.

DRYWALL

Wipe down with a damp cloth to remove residual joint compound dust prior to priming. No primer is required when hanging strippable fabric backed vinyl wallcovering over bare drywall. However, adhesive must fully cure (approximately 4-6 weeks) prior to stripping. If uncertain, priming is always recommended to ensure proper performance.

PLASTER

New plaster must age at least 90 days before hanging wallcovering. Prime prior to installation.

GLOSSY SURFACES

Glossy paint, paneling, metal, glass, plastic, etc. should be primed with ShieldZ Universal, ShieldZ Universal Plus, ShieldZ Clear Acrylic Wall Size or ShieldZ Oil-Base Wallcovering Primer prior to wallcovering installation. Metal surfaces should be primed with rust inhibiting Bulls-Eye® 1-2-3 Primer.

EXISTING VINYL WALLCOVERING

This product is not intended for hanging wallcoverings over existing vinyl wallcoverings without the use of a primer. For hanging directly over vinyl without priming, use SureGrip 127 Vinyl over Vinyl Wallcovering Adhesive according to label directions. For hanging lightweight wallpaper or borders directly over unprimed vinyl, use SureGrip Universal Adhesive or SureGrip Border Adhesive for Wallpapered Surfaces.

TEXTILE/DELICATE/POLYOLEFIN/POLYESTER BACKED WALLCOVERINGS

Take special care to keep the adhesive off the face of textile or delicate wallcovering. Some wallcovering can be stained by water alone. Test for stain resistance prior to installation and hang according to manufacturer's instructions.



SUREGRIP® 122 HEAVY DUTY CLEAR STRIPPALBE WALLCOVERING ADHESIVE

PRODUCT APPLICATION (cont.)

APPLICATION

Use only when temperature is between 50-100°F (10-38°C) and the relative humidity is less than 85%. Adhesive is ready to use but may be thinned with a maximum of 1 pint of water per gallon of adhesive for use with lightweight non-pasted or pre-pasted wallpaper. Apply an even coat using a roller, brush or pasting machine to the back of the wallcovering. Make sure sufficient adhesive is on edges. Avoid contact with the surface of embossed or delicate wallcovering. Book and hang wallcovering according to the manufacturer's instructions.

COVERAGE

One gallon of adhesive will hang up to 4 to 5 double rolls or 280 square feet. Spread rate may differ with various backings.

CLEAN-UP

Remove excess adhesive on or around the wallcovering immediately with clean water. Additional effort may be required if adhesive is allowed to contact the surface of embossed or textured vinyl. Close container tightly after each use.

TOOL CLEAN-UP

Clean tools with warm water.

STORAGE

Protect from freezing. Always keep the container tightly closed and store in a cool dry place at temperatures between 40-100°F (4-38°C).



SUREGRIP® 122 HEAVY DUTY CLEAR STRIPPABLE WALLCOVERING ADHESIVE

PHYSICAL PROPERTIES

		SUREGRIP 122 HEAVY DUTY CLEAR STRIPPABLE WALLCOVERING ADHESIVE
Resin Type		Starch-based Adhesive
Solvents		Water
Appearance		Clear
Odor		Mild
Weight	Per Gallon	10.7 lbs.
	Per Liter	1.28 kg
Solids	By Weight	50.0-51.0%
	By Volume	36.0-37.0%
Volatile Organic Compounds		<10 g/l (0.083 lbs./gal.)
Practical Coverage at Recommended DFT (assumes 15% material loss)		280 sq. ft./gal. (4 to 5 double rolls) Depending on porosity and application method
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity		Drying time will vary depending on the wallcovering type, temperature, ventilation and humidity in the room.
Shelf Life		1 year
Flammability		Non-flammable
Flash Point		>200°F (93°C)
Safety Information		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.