
1. Identification

Product identifier CUTEK® Wood Reviver**Other means of identification** Not available.**Recommended use** Wood Cleaner**Recommended restrictions** None known.**Manufacturer/Importer/Supplier/Distributor information****Distributor**

Company name	CUTEK America LLC	Deck Source Inc.
Address	6810 Tordera St Coral Gables, FL 33146 USA	22 Winstar Rd, Unit 1 Oro-Mednote, ON L0L 2E0 Canada

Telephone 1-833-MY-CUTEK (1-833-692-8835)**E-mail** Not available.**Emergency phone number** **EMERGENCY CONTACT:** 1-855-237-5573
POISON CONTROL HOTLINE: 1-800-222-1222

2. Hazard identification

Physical hazards Corrosive to metals Category 1**Health hazards** Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 1

Environmental hazards Not classified.**WHMIS 2015 defined hazards** Not classified**Label elements****Signal word** Danger**Hazard statement** May be corrosive to metals. Causes skin irritation. Causes serious eye damage.**Precautionary statement****Prevention** Keep only in original packaging. Do not breathe mist or vapor. Wash thoroughly after handling. Wear protective gloves, eye protection, and face protection.**Response** Absorb spillage to prevent material-damage. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash it before reuse. Specific treatment (see information on this label). IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.**Storage** Store in a corrosion resistant container with a resistant inner liner.**Disposal** Dispose of container in accordance with local, regional, national and international regulations.**WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC)** None known**WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC)** None known**Hazard(s) not otherwise classified (HNOC)** None known.**Supplemental information** None.

3. Composition/Information on ingredients

Mixture

Chemical name	Common name and synonyms	CAS number	%
Ethanedioic acid, dihydrate		6153-56-6	5 - 10 *
Ethanol, 2-butoxy-		111-76-2	1 - 5 *
Sodium dodecylbenzene sulfonate		25155-30-0	0.1 - 1 *

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments	US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200. *CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret.
-----------------------------	--

4. First-aid measures

Inhalation	If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.
Skin contact	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Ingestion	Rinse mouth. Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Never give anything by mouth if victim is unconscious or is convulsing. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.
Indication of immediate medical attention and special treatment needed	Treat patient symptomatically.
General information	If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance. Do not get in eyes, on skin or clothing. Keep out of reach of children.

5. Fire-fighting measures

Suitable extinguishing media	Foam. Powder. Carbon dioxide.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.
Hazardous combustion products	May include and are not limited to: Oxides of carbon.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb spillage to prevent material damage. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. Prevent entry into waterways, sewer, basements or confined areas.
Environmental precautions	Do not discharge into lakes, streams, ponds or public waters.

7. Handling and storage

Precautions for safe handling	Do not get in eyes, on skin, or on clothing. Wear appropriate personal protective equipment. Provide adequate ventilation. Observe good industrial hygiene practices. Wash thoroughly after handling. When using do not eat or drink.
Conditions for safe storage, including any incompatibilities	Store in a corrosion resistant container with a resistant inner liner. Store in a cool, dry place out of direct sunlight. Store away from incompatible materials (see Section 10 of the SDS). Keep out of reach of children.

8. Exposure controls/Personal protection

Occupational exposure limits

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value
Ethanedioic acid, dihydrate (CAS 6153-56-6)	STEL	2 mg/m3
	TWA	1 mg/m3
Ethanol, 2-butoxy- (CAS 111-76-2)	TWA	97 mg/m3
		20 ppm

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value
Ethanedioic acid, dihydrate (CAS 6153-56-6)	STEL	2 mg/m3
	TWA	1 mg/m3
Ethanol, 2-butoxy- (CAS 111-76-2)	TWA	20 ppm

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value
Ethanedioic acid, dihydrate (CAS 6153-56-6)	STEL	2 mg/m3
	TWA	1 mg/m3
Ethanol, 2-butoxy- (CAS 111-76-2)	TWA	20 ppm

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value
Ethanedioic acid, dihydrate (CAS 6153-56-6)	STEL	2 mg/m3
	TWA	1 mg/m3
Ethanol, 2-butoxy- (CAS 111-76-2)	TWA	20 ppm

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Components	Type	Value
Ethanedioic acid, dihydrate (CAS 6153-56-6)	STEL	2 mg/m3
	TWA	1 mg/m3

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)

Components	Type	Value
Ethanedioic acid, dihydrate (CAS 6153-56-6)	15 minute	2 mg/m3
	8 hour	1 mg/m3
Ethanol, 2-butoxy- (CAS 111-76-2)	15 minute	30 ppm
	8 hour	20 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Ethanedioic acid, dihydrate (CAS 6153-56-6)	PEL	1 mg/m3
Ethanol, 2-butoxy- (CAS 111-76-2)	PEL	240 mg/m3
		50 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Ethanedioic acid, dihydrate (CAS 6153-56-6)	STEL	2 mg/m3
	TWA	1 mg/m3

US. ACGIH Threshold Limit Values

Components	Type	Value
Ethanol, 2-butoxy- (CAS 111-76-2)	TWA	20 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Ethanedioic acid, dihydrate (CAS 6153-56-6)	STEL	2 mg/m3
	TWA	1 mg/m3
Ethanol, 2-butoxy- (CAS 111-76-2)	TWA	24 mg/m3
		5 ppm

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Ethanol, 2-butoxy- (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines See above

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Ethanol, 2-butoxy- (CAS 111-76-2) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Ethanol, 2-butoxy- (CAS 111-76-2) Can be absorbed through the skin.

Appropriate engineering controls Ensure adequate ventilation.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection

Hand protection Rubber gloves. Confirm with a reputable supplier first.

Other As required by employer code.

Respiratory protection Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

Thermal hazards Not applicable.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke.

9. Physical and chemical properties

Appearance	Liquid
Physical state	Liquid.
Form	Liquid.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
pH	1.1
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Pour point	Not available.
Specific gravity	1.09 @ 21°C
Partition coefficient (n-octanol/water)	Not available.
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not available.

Flammability limit - upper (%) Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies) Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

10. Stability and reactivity

Reactivity May react with incompatible materials.

Possibility of hazardous reactions No dangerous reaction known under conditions of normal use.

Chemical stability Material is stable under normal conditions.

Conditions to avoid Do not mix with other chemicals.

Incompatible materials Strong oxidizing agents. Metals.

Hazardous decomposition products May include and are not limited to: Oxides of carbon.

11. Toxicological information

Routes of exposure Eye, Skin contact, Inhalation, Ingestion.

Information on likely routes of exposure

Ingestion May cause stomach distress, nausea or vomiting.

Inhalation Prolonged inhalation may be harmful.

Skin contact Causes skin irritation.

Eye contact Causes serious eye damage.

Symptoms related to the physical, chemical and toxicological characteristics Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Information on toxicological effects**Acute toxicity**

Components	Species	Test Results
Ethanedioic acid, dihydrate (CAS 6153-56-6)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	20000 mg/kg, ECHA
<i>Inhalation</i>		
LD50	Not available	
<i>Oral</i>		
LD50	Rat	375 mg/kg, ECHA 9.5 ml/kg, ECHA, male 7.5 ml/kg, ECHA, female
Ethanol, 2-butoxy- (CAS 111-76-2)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg, 24 Hours, ECHA

Components	Species	Test Results
<i>Inhalation</i>		
LC50	Rat	450 ppm, 4 Hours, ECHA
<i>Oral</i>		
LD50	Guinea pig	1414 mg/kg, ECHA
Sodium dodecylbenzene sulfonate (CAS 25155-30-0)		
Acute		
<i>Dermal</i>		
LD50	Rat	> 2000 mg/kg, ECHA
<i>Inhalation</i>		
LC50	Not available	
<i>Oral</i>		
LD50	Rat	650 mg/kg, ECHA
Skin corrosion/irritation	Causes skin irritation.	
Exposure minutes	Not available.	
Erythema value	Not available.	
Oedema value	Not available.	
Serious eye damage/eye irritation	Causes serious eye damage.	
Corneal opacity value	Not available.	
Iris lesion value	Not available.	
Conjunctival reddening value	Not available.	
Conjunctival oedema value	Not available.	
Recover days	Not available.	
Respiratory or skin sensitization		
Canada - Alberta OELs: Irritant		
Ethanedioic acid, dihydrate (CAS 6153-56-6)	Irritant	
Ethanol, 2-butoxy- (CAS 111-76-2)	Irritant	
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP or OSHA.	
ACGIH Carcinogens		
Ethanol, 2-butoxy- (CAS 111-76-2)	A3 Confirmed animal carcinogen with unknown relevance to humans.	
Canada - Manitoba OELs: carcinogenicity		
Ethanol, 2-butoxy- (CAS 111-76-2)	Confirmed animal carcinogen with unknown relevance to humans.	
Canada - Quebec OELs: Carcinogen category		
Ethanol, 2-butoxy- (CAS 111-76-2)	Detected carcinogenic effect in animals.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Ethanol, 2-butoxy- (CAS 111-76-2)	Volume 88 - 3 Not classifiable as to carcinogenicity to humans.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)		
Not listed.		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Teratogenicity	Not available.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Prolonged inhalation may be harmful.	

12. Ecological information

Ecotoxicity	See below
--------------------	-----------

Ecotoxicological data		Species		Test Results
Components				
Ethanedioic acid, dihydrate (CAS 6153-56-6)				
Crustacea	EC50	Daphnia		137.5 mg/L, 48 Hours
Aquatic				
Crustacea	EC50	Water flea (Daphnia magna)		125 - 150 mg/L, 48 hours
Ethanol, 2-butoxy- (CAS 111-76-2)				
Crustacea	EC50	Daphnia		1819 mg/L, 48 Hours
Aquatic				
Fish	LC50	Inland silverside (Menidia beryllina)		1250 mg/L, 96 hours
Sodium dodecylbenzene sulfonate (CAS 25155-30-0)				
Aquatic				
Crustacea	EC50	Water flea (Ceriodaphnia dubia)		3.26 - 14.51 mg/L, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)		3.2 - 5.6 mg/L, 96 hours
Persistence and degradability		No data is available on the degradability of this product.		
Bioaccumulative potential				
Mobility in soil		No data available.		
Mobility in general		Not available.		
Other adverse effects		No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		

13. Disposal considerations

Disposal instructions	Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	D002: Waste Corrosive material [pH <=2 or >=12.5, or corrosive to steel] The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

Transport of Dangerous Goods (TDG) Proof of Classification	Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.
---	--

U.S. Department of Transportation (DOT)

Basic shipping requirements:

UN number	UN1760
Proper shipping name	Corrosive liquids, n.o.s.
Technical name	Ethanedioic acid, dihydrate
Hazard class	8
Packing group	III
Special provisions	IB3, T7, TP1, TP28
Packaging exceptions	< 1.3 gal- Limited Quantity
Packaging non bulk	203
Packaging bulk	241

Transportation of Dangerous Goods (TDG - Canada)

Basic shipping requirements:

UN number	UN1760
Proper shipping name	CORROSIVE LIQUID, N.O.S.
Technical name	Ethanedioic acid, dihydrate
Hazard class	8
Packing group	III
Special provisions	16
Packaging exceptions	< 5L - Limited Quantity



15. Regulatory information

Canadian federal regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Canada CEPA Schedule I: Listed substance

Ethanol, 2-butoxy- (CAS 111-76-2) Listed.

Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number

Ethanol, 2-butoxy- (CAS 111-76-2) 1 TONNES

Canada Priority Substances List (Second List): Listed substance

Ethanol, 2-butoxy- (CAS 111-76-2) Listed.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

WHMIS 2015 Exemptions

Not applicable

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Ethanol, 2-butoxy- (CAS 111-76-2) Listed.

Sodium dodecylbenzene sulfonate (CAS 25155-30-0) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

No

SARA 311/312 Hazardous chemical

Yes

Classified hazard categories

Corrosive to metal
Skin corrosion or irritation
Serious eye damage or eye irritation

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Ethanol, 2-butoxy- (CAS 111-76-2)

Not regulated.

US state regulations

See below

US - California Hazardous Substances (Director's): Listed substance

Ethanedioic acid, dihydrate (CAS 6153-56-6)	Listed.
Ethanol, 2-butoxy- (CAS 111-76-2)	Listed.
Sodium dodecylbenzene sulfonate (CAS 25155-30-0)	Listed.

US - Illinois Chemical Safety Act: Listed substance

Ethanol, 2-butoxy- (CAS 111-76-2)
Sodium dodecylbenzene sulfonate (CAS 25155-30-0)

US - Louisiana Spill Reporting: Listed substance

Ethanol, 2-butoxy- (CAS 111-76-2)	Listed.
Sodium dodecylbenzene sulfonate (CAS 25155-30-0)	Listed.

US - Minnesota Haz Subs: Listed substance

Ethanedioic acid, dihydrate (CAS 6153-56-6)	Listed.
Ethanol, 2-butoxy- (CAS 111-76-2)	Listed.

US - Texas Effects Screening Levels: Listed substance

Ethanedioic acid, dihydrate (CAS 6153-56-6)	Listed.
Ethanol, 2-butoxy- (CAS 111-76-2)	Listed.
Sodium dodecylbenzene sulfonate (CAS 25155-30-0)	Listed.

US. Massachusetts RTK - Substance List

Ethanedioic acid, dihydrate (CAS 6153-56-6)
Ethanol, 2-butoxy- (CAS 111-76-2)
Sodium dodecylbenzene sulfonate (CAS 25155-30-0)

US. New Jersey Worker and Community Right-to-Know Act

Ethanedioic acid, dihydrate (CAS 6153-56-6)
Ethanol, 2-butoxy- (CAS 111-76-2)
Sodium dodecylbenzene sulfonate (CAS 25155-30-0)

US. Pennsylvania Worker and Community Right-to-Know Law

Ethanedioic acid, dihydrate (CAS 6153-56-6)
Ethanol, 2-butoxy- (CAS 111-76-2)
Sodium dodecylbenzene sulfonate (CAS 25155-30-0)

US. Rhode Island RTK

Ethanedioic acid, dihydrate (CAS 6153-56-6)
Ethanol, 2-butoxy- (CAS 111-76-2)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

Inventory status


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	/ 3
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X



Disclaimer

Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date	16-February-2022
Version #	01
Effective date	07-February-2022
Prepared by	Dell Tech Laboratories Ltd. Phone: (519) 858-5021
Further information	Not available.
Other information	For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.