



LIFT



WIPE



DRY

**HYDROACTION**  
POLYURETHANE™

**CLEANS UP WITH WATER**

WITHIN 5 MIN. OF APPLICATION



**GAPS & CRACKS**

Lifted & wiped with dry cloth



Wiped with wet cloth



✓ Wipes clean with water within 5 min.

**Traditional Polyurethane Foam**

Lifted & wiped with dry cloth



Wiped with wet cloth



✗ Sticky residue, ruined surface

**CLEANABLE SUBSTRATES**



Non-Porous Surfaces



Finished Hardwood Flooring



Porcelain Tile



Most Metals & Plastics



Painted Surfaces



Vinyl/ Laminate

- »» **POLYURETHANE STRENGTH**
- »» **DURABLE AIR-TIGHT SEAL**
- »» **ALL SEASON APPLICATION**
- »» **SAVES TIME & LABOR**
- »» **REUSABLE FOR MORE PROJECTS**

**IDEAL FOR:**

- Plumbing Fixtures
- Exhaust Vents
- Electrical Outlet Boxes
- Through Penetrations
- Attics
- HVAC/Ducts
- Baseboards
- Sill Plates
- Rim Joists

**ADHERES TO:**

- Wood
- Drywall/Gypsum
- Concrete & Masonry
- Most Metals
- Plastic
- Painted Surfaces



| Description             | Size     | Color     | Case Pack | Product Code    | GTIN 14           | Case Weight (lb) | Case Dimensions (LxWxH) | Case Volume (cu ft) | Cases Per Pallet |
|-------------------------|----------|-----------|-----------|-----------------|-------------------|------------------|-------------------------|---------------------|------------------|
| DAP® GAPS & CRACKS FOAM | 12 FL OZ | Off-White | 12        | 0 75650 00085 4 | 100 75650 00085 1 | 12.87            | 11.50" x 8.5" x 9.0"    | 0.509               | 108              |



# GAPS & CRACKS HIGH DENSITY FOAM



»» HYDROACTION ««  
POLYURETHANE™

**CLEANS UP WITH WATER**

WITHIN 5 MIN. OF APPLICATION

**DAP® GAPS & CRACKS HIGH DENSITY FOAM** delivers professional performance with its air-tight seal, excellent adhesion and all-around versatility. Get the strength and durability of polyurethane foam with the ease of water clean-up—no mess, no hassle! This revolutionary, patent pending formula makes jobs faster, cleaner and more efficient.

**SEALS & INSULATES  
GAPS UP TO 1" WIDE**

**HIGH STRENGTH DURABILITY**

**WIDE TEMP. APPLICATION  
25° TO 105°F**



LEARN MORE

