



GRADE: Gun Foam 

COLOR: Orange Foam 

GUN FOAM II

FIREBLOCK FOAM SEALANT

Touch 'n Seal® Gun Foam II Foam Sealant is a high-performance, 1-Component, approved Type V residential fireblock sealant for use in filling annular spaces around penetrations for approved fire blocking performance.

FIRE RATED • MULTI-PURPOSE

- Type V residential fireblock sealant
- Distinctive orange color
- ICC-ES ESR-1926 approved
- Application temperature range 60°F to 100°F (16°C to 38°C)
- Class A fire rated
- Interior and exterior use

IDEAL FOR

- Cracks & Gaps up to 1 1/2" (38 mm)
- Fireblocking & Insulating
- Around Pipe Conduit Penetrations

TECH DATA

Density:	1.3 - 1.8 pcf
R-Value:	4-5/in (25mm)
Tack-Free:	10 minutes
Cuttable:	Approx. 30 minutes
Cure:	1 hour
ASTM E84:	Flame Spread 15 Smoke Developed 25
Yield (1/4" bead):	3,200 linear ft
Shelf Life:	18 months



Product #	Size	Color	UPC	GTIN 14	Case Pk	Case Weight (lb)	Case Vol. (cu ft)	Case Dimensions (LxWxH)	Case Per Pallet
7565000121	24 oz	Orange	0 75650 00121 9	100 75650 00121 6	12	23.8	0.641	11"x 8.75"x 11.5"	72

FIREBLOCK FOAM SEALANT