



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® TOUCH 'N SEAL® PEST CONTROL SPECIALTY FOAM SEALANT – GRAY

PRODUCT DESCRIPTION

DAP® Touch n' Seal® PEST CONTROL blocks mice, and other pests from entering the home. The expanding polyurethane foam sealant seals cracks and gaps up to 1.5" (38mm) wide to block drafts and moisture resulting in improved comfort and reduced energy usage.



Meets ASTM E84/UL 723, Class A Fire Rated, UL Classified

PACKAGING	Case	COLOR	UPC
24 oz (566g) Can	12	Gray	7565000125

KEY FEATURES & BENEFITS

- Minimal expansion resists bowing frames and jambs
- Seals against air, moisture and blocks mice and other pests
- Bonds to common building materials including wood, concrete, insulating foam boards, metal, plastics, and sheetrock

5/7/2020



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

- Easy to control gun foam applicator
- ICC Listed (ES ESR-1926)
- Meets ASTM E84, and UL-Listed
- Meets AAMA standards 812-04 for low pressure foams
- Class A fire rated
- Gray color
- Interior / exterior use (When coated)

SUGGESTED USES

USE TO FILL AND SEAL:

- Window and door frames / jambs
- Gaps and cracks in foundations, crawlspaces, attics, and basements
- Partitions and stud walls

FOR BEST RESULTS

- Apply in temperatures between 20°F - 120°F (-6°C to 48°C)
- Surface must be free of oil and dirt for adhesion
- Dispense in the UPSIDE-DOWN position
- Apply in spaces with 40% relative humidity or greater
- Use around, not inside, junction boxes

APPLICATION

DIRECTIONS: Important – read all directions and cautions before use. Always wear gloves, eye protection and work clothes. Use drop cloths. Product is flammable during dispensing – turn off sources of ignition prior to use. Always refer to local building codes prior to application of Touch ‘N Foam sealants.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

Preparation: To promote adhesion surface must be free of oil and dirt. For easy attachment to foam applicator gun, apply petroleum jelly to the gun basket before screwing on can. While pointing in a safe direction, depress trigger and attach gun to can (see instructions inside gun box). Do not over-tighten. Important: Before starting the job, first practice dispensing onto scrap materials.

Application: For best results this product should only be dispensed in the UPSIDE_DOWN position and apply in spaces with 40% greater relative humidity. Fill gap no more than 1/4 full, allowing room for expansion. Foam will be tack-free in about 5 minutes (50% RH). Do not overfill. Excess foam can be trimmed, sanded, caulked or plastered as necessary. Direct sunlight discolors foam if not painted or covered.

Can Replacement: While pointing the gun in a safe direction, depress trigger and quickly remove empty can. Spray basket with polyurethane foam cleaner and immediately replace with a new can of foam to prevent foam from hardening in the gun.

Clean-up: If wet foam contacts skin, clean immediately with a dry rag – do not use water – water accelerates curing. Cured foam must be removed mechanically from surfaces. Uncured foam can be cleaned from most surfaces with Foam Cleaner or acetone. Do not attempt to remove cured solvents. If foam dries on skin, apply generous amounts of petroleum jelly, put on plastic gloves and wait 1 hour. With a clean cloth, firmly wipe off residue and repeat process if necessary. DO NOT use acetone or other solvents to remove product from skin.

Storage/Re-Use: Turn gun's flow control knob to closed position and store can in upright position (with gun still attached). To restart, shake well for 30 seconds, turn flow control knob to open position and dispense foam. Maximum Storage: 15 days. Store can upright below 90° F (33°C).

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Yield per can (1/4" bead) ASTM C1536	1972 linear feet
Dry Time/ tack free	5 minutes
Fully Cured	4 hours
Shelf Life	18 months (unopened)
Application Temperature Range	20°F to 120°F (-6°C to 48°C)
Cuttable	Approx. 18 mins
ASTM C-518 R-Value	4-5/in (25mm)
Water Resistant (ASTM D2842)	<1.5% at 4 Days
International Building Code	Compliant
International Residential Code	Compliant
California Bureau of Home Furnishings and Insulation	Compliant
ICC Evaluation	ESR 1926



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

UL Classified Caulking & Sealants	Listed
UL 723 Surface Burning Characteristics Fire Test (Flame/Smoke)	10/15

SAFETY

See product label or Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or calling 888-DAP-TIPS.

LIMITED WARRANTY

LIMITED WARRANTY: If the product fails to perform when used as directed, within one year from the date of purchase, call 888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP Global Inc. will not be responsible for incidental or consequential damages.

COMPANY IDENTIFICATION

Manufacturer: DAP Global Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call 888-DAP-TIPS or visit dap.com & click on “Ask the Expert”

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

Also visit the DAP website at dap.com

R14175
1L15



UNDERWRITERS LABORATORIES INC.
CLASSIFIED CAULKING AND SEALANT
Surface Burning Characteristics
Applied To Inorganic Reinforced
Cement Board*
Flame Spread 10
Smoke Developed 15

*TESTED AS APPLIED IN THREE 1/2" DIAMETER
BEADS 5" ON CENTER COVERING 11.1% OF THE
EXPOSED TEST SAMPLE AREA.