




Preserva Wood®
Transparent and Semi-transparent Wood Stain



PRODUCT DATA SHEET

Product Description

Preserva Wood® Transparent Wood Stain and Sealer allows your paint professional to apply our penetrating oil based stain and sealer in a variety of pre-tinted colors. This natural oil based stain with transparent oxide pigments offers superior protection for your wood, while highlighting it's natural beauty.

Surfaces to Stain

- New or existing exterior wood (smooth and rough)
- Fences
- Decks
- Wood siding
- Log homes
- Shake or shingles

Coverage

Smooth wood (deck boards)
350-400 square feet per gallon

Rough Wood (fence boards)
175-225 square feet

Technical Information

Base: Alkyd resin
Solvent: Mineral Spirits
Dry time: 24-48 hours depending on temperature and humidity.
% Solids by weight 72-73%
Weight 7.4-7.6 lbs/gal
Pigment type Organic
VOC less than 250 g/l

Warranty

If you are not completely satisfied with the performance of this product when applied to a properly prepared surface according to label directions, manufacturer will replace the product or refund the purchase price at the manufacturer's option. Proof of purchase required, photograph and complaint description.

Surface Preparation

Proper surface preparation is essential to assure maximum performance. Preserva Wood® must be able to penetrate into the wood. Wood must be clean and dry prior to staining. Heavy or wet boards should be allowed to air dry for 3 weeks before staining. Persistent black spots that appear when wood is wet are mold or mildew. Use an approved product to kill mold and mildew before staining. Dirt and pollen should be cleaned from wood surfaces using a mild cleanser, water and a deck brush or low output pressure washer. All previous coatings that prevent penetration must be removed.

Mix

Stir stain well and stir often during use, making sure all pigment has been well mixed before using.

Test

Test stain for penetration and appearance before staining.





Preserva Wood® Transparent and Semi-transparent Wood Stain



PRODUCT DATA SHEET

Application

Be sure the weather will be dry for at least 24 hours before and after applying the stain. Apply to deck boards and other smooth wood with an oil based brush or stain pad. Use a pump sprayer to apply to vertical surfaces, followed by back brushing. Do not use paint rollers! Apply only as much stain as will readily absorb into the wood. Apply **ONE COAT ONLY!** Treat full length of boards, keeping a wet edge. Apply stain to cool, dry wood, when temperatures are between 60 and 90 degrees F. Do not apply in the heat of the day. Use a rag to remove all excess stain (shine) from the surface of the wood within 20 minutes of application. **DO NOT ALLOW STAIN TO PUDDLE AND CURE ON THE SURFACE OF THE WOOD!** Place oil soaked rags, clothing and other application materials in water immediately after use.

FOR WOOD SUBSTRATES ONLY!

Cleanup and Disposal

Soak oily rags, clothes, or any other material in a water filled sealed container to avoid spontaneous combustion (fire). After one week, wring out and lay flat to air dry outdoors, away from wood, paper or any combustible material. Do not throw away until completely dry. Tools and equipment should be cleaned with paint thinner. Seal partial containers tightly when not in use. Store in a cool, dry place with no source of ignition. Dispose of empty cans in accordance with local, state and federal laws.

Warning

Rags, steel wool, or waste soaked with Preserva Wood® may spontaneously catch fire if improperly discarded. Immediately after each use, place rags, steel wool, and waste in a sealed, water filled metal container.

Maintenance

Clean all exterior wood with a mild detergent based cleaner. Simply clean, check for mildew and re-treat with a light application when wood is dry and will absorb more stain. **DO NOT over-apply.**

Lead Warning

WARNING! If you scrape, sand or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should avoid exposure. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log onto

www.epa.gov/lead

Contact Us

1-800-797-2537

info@preservaproducts.com

Preserva Products, Ltd.

12860 Earhart Avenue

Auburn, CA 95602

