



Architectural Coatings

PPG ProLuxe Interior Lacquer Spray Clear Wood Finish

**GENERAL DESCRIPTION**

ProLuxe Interior Lacquer Clear Wood Finish is the brand to trust for an outstanding, fast drying, and easy-to-use finish for any interior wood project. Today's professionals and enthusiasts alike continue to appreciate its "forgiving nature", as well as, its crystal clear finish and fast drying time.

**RECOMMENDED SUBSTRATES**

Wood Cabinets	Wood Molding
Wood Furniture	Wood Trim
Wood Doors	Decorative Metals

**FEATURES / BENEFITS**

SAME DEFT® FORMULA, NEW NAME  
Excellent Lacquer Spray  
Finishes and Restores Furniture  
Beautifies Wood and Metal  
Fast Dry  
For Furniture, Cabinets, Trim, Brass railings and decorative metals  
Resists alcohol, water and other common household spills

**CONFORMANCE STANDARD**

VOC compliant – lower than Federal AIM

**PRODUCT INFORMATION**

PLX010S	Clear Gloss
PLX011S	Clear Semi-Gloss
PLX017S	Clear Satin

**LIMITATIONS OF USE**

FOR INTERIOR USE ONLY. Apply when air and surface temperature is between 50°F (10°C) and 90°F (32°C).

Do not apply over varnishes, enamels or other products that dry by oxidation; it may result in lifting or wrinkling.

DO NOT USE ON FLOORS OR FOR EXTERIOR APPLICATIONS.

**PRODUCT DATA**

<b>PRODUCT TYPE:</b>	Lacquer
<b>SHEEN:</b>	Gloss, 90-100 @ 60° Semi-Gloss 28-32 @ 60° Satin, 12-18 @ 60°
<b>VOLUME SOLIDS*:</b>	11% +/- 2%
<b>WEIGHT SOLIDS*:</b>	16% +/- 2%
<b>WEIGHT/GALLON*:</b>	7.2 lbs. (3.3 kg) +/- 0.2 lbs. (91 g)
<b>MAX PWMIR CCP:</b>	< 1.50

\*Product data calculated on product PLX010S.

**COVERAGE:** One can covers approximately 60 sq. ft. (5.6 sq. meters). Coverage figures do not include material loss due to surface irregularities and porosity, or material loss due to application method.

**DRYING TIME:** Dry time @ 77°F (25°C); 50% relative humidity.  
To Touch: 10 minutes  
To Recoat: 30 minutes  
To Service: 24 hours

Drying times listed may vary depending on temperature, humidity, film build, and air movement.

**CLOGGING:** If spray button becomes clogged, wear eye protection and wipe off the button opening with acetone—DO NOT stick pin in spray button opening.

**CLEANUP:** When finished spraying, hold can upside down and spray until clear gas appears, then wipe off tip before storing. Clean up wet paint with acetone. DANGER - RAGS, STEEL WOOL OR WASTE SOAKED WITH PROLUXE CLEAR WOOD FINISH MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER.

**DISPOSAL:** Contact your local environmental regulatory agency for guidance on disposal of empty can. Do not burn or place in home trash compactor.

**FLASH POINT:** 53°F (11.67°C)

**PACKAGING**

Aerosol Net Wt. 12.25 oz. (347 g)

**GENERAL SURFACE PREPARATION**

Clean surface thoroughly and sand with fine 220-grit sandpaper. Remove all dust.

**NEW OR BARE WOOD:** Stain if desired. When applying over stained wood, ensure stain is compatible with lacquer finishes and is thoroughly dry. Sand with 220-grit sandpaper along the wood grain until smooth. Remove all dust.

**PREVIOUSLY COATED WOOD:** Test in a small area. If it wrinkles or lifts, strip to bare wood. If the finish is damaged or deteriorated, complete removal of the finish is recommended. If the clean surface is in good condition, sand with 220-grit sandpaper. Remove all dust.

**BARE OR UNCOATED METAL:** Clean surface thoroughly and allow to dry prior to application.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted, NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

**APPLICATION INFORMATION**

Cover nearby surfaces, eliminate ignition sources, and wear safety glasses. USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN. Read all label and Safety Data Sheet (SDS) information prior to use. SDS are available through our web site or by calling 1-800-441-9695.

Shake the can for 1 minute. Spray 6-10 inches from surface. Apply a thin coat and allow it to dry. Recoat in 30 minutes. Recoat 3 or more times. After each use, clear valve by holding can upside down and spraying until only clear gas comes out.

**Permissible temperatures during application:**

Material: 50 to 90°F    10 to 32°C    Ambient: 50 to 90°F    10 to 32°C    Substrate: 50 to 90°F    10 to 32°C

**PRECAUTIONS**

**DANGER! FLAMMABLE LIQUID AND VAPOR. HARMFUL IF INHALED. HARMFUL IF ABSORBED THROUGH SKIN. HARMFUL OR FATAL IF SWALLOWED. CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION.** Sanding and grinding dusts may be harmful if inhaled. Inhalation of high concentrations of vapor may affect the central nervous system. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. High vapor concentrations can cause headaches, dizziness, drowsiness and nausea and may lead to unconsciousness. The product may not be stable under certain conditions of storage or use: high temperature/pressure hazard. Can enter lungs and cause damage. Keep away from heat, sparks and flame. Do not breathe vapor or mist. Do not swallow. Do not get on skin or clothing. Avoid contact with eyes. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. **DANGER - RAGS, STEEL WOOL OR WASTE SOAKED WITH PROLUXE CLEAR WOOD FINISH MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER. Note: These warnings encompass the product series. Prior to use, read and follow product-specific SDS and label information. FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. In case of contact, immediately flush skin with plenty of water while removing contaminated clothing and shoes. Get medical attention immediately. If inhaled, remove to fresh air. Call physician immediately. Keep out of the reach of children. For workplace use, an SDS is available from your retailer or by calling (412) 492-5555. EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.).

© 2023 PPG Industries, Inc. All Rights Reserved. The PPG Logo is a registered trademark of PPG Industries Ohio, Inc. ProLuxe is a registered trademark of PPG Architectural Finishes, Inc. Deft & Horseshoe Design are registered trademarks of PRC-Desoto International, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate: however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-441-9695.



PPG Architectural Finishes, Inc.  
One PPG Place  
Pittsburgh, PA 15272  
[www.ppgpaints.com](http://www.ppgpaints.com)  
[www.perfectwoodstains.com](http://www.perfectwoodstains.com)

Technical Services  
1-800-441-9695

Architect/Specifier  
1-888-PPG-IDEA

PPG Architectural Coatings Canada Inc.  
1550 rue Ampère, Suite 500  
Boucherville (Quebec) J4B 7L4

PLX010S 1/2024