THINNER	TECHNICAL DATA	RPS-07

RUST-OLEUM PROFESSIONAL SOLUTIONS

MEK SOLVENT BLEND

DESCRIPTION AND USES

Rust-Oleum® Professional Solutions MEK Solvent Blend is a unique blend of solvents designed to be used to thin and clean up urethanes and epoxies. This solvent can also be used to clean surfaces and equipment.

This product was formerly known as 190 Urethane Thinner.

PRODUCT

SKU	DESCRIPTION (Gallon)
190402	MEK Solvent Blend

PRODUCT APPLICATION

APPLICATION

Use as a thinner when recommended by the product manufacturer. Always follow the paint manufacturer's instructions for proper reduction ratios. Do not use more than recommended. Protect hands with solvent-resistant gloves and eyes with safety glasses. Most finishes require a specific thinner for use within certain temperature ranges.

DIRECTIONS

Add gradually and stir thoroughly until desired consistency is obtained. Excessive amounts may decrease gloss, viscosity and hiding power. Clean brushes, spray equipment, rollers, and trays as long as finish remains wet on these tools.

PHYSICAL PROPERTIES

		MEK SOLVENT BLEND
Composition		Ethyl Acetate, Methyl Ethyl Ketone (MEK), Ester solvent EEP
Weight	**Per Gallon**	7.26 lbs
	Per Liter	0.87 kg
VOC		870 g/L
Shelf Life		5 Years
Flash Point		-5°C (23°F)
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

RUST-OLEUM

Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061

Phone: 877·385·8155
www.rustoleum.com/industrial

Form: EJ-146
Rev.: 032024