

FROGTAPE® PRO GRADE ORANGE PAINTER'S TAPE®

TYPICAL APPLICATIONS

- For interior or exterior use on a variety of surfaces even in hot and humid conditions

PRODUCT FEATURES

- High adhesion
- Conformable backing
- 3-day clean removal without shredding
- Withstands direct outdoor sunlight for up to 1 day
- Sticks better than beige®
- DOES NOT contain PaintBlock® Technology
- *Test before use on all surfaces and when using solvent-based coatings

CONSTRUCTION

Backing: Crepe paper

Adhesive: Rubber-based adhesive

STANDARD WIDTHS

0.94 in; 1.41 in; 1.88 in

24 mm; 36 mm; 48 mm

STANDARD LENGTH

60.1 yd

55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

NA

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



PHYSICAL PROPERTIES

Adhesion to Stainless Steel

Elongation

Service Temperature Range

Tensile

Thickness

STANDARD

39 oz/in width

9%

50 F to 200 F

24 lbs/in width

6.4 mils

METRIC

4.27 N/10 mm

9%

10 C to 93 C

42.0 N/10 mm

0.16 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.



The mark of responsible forestry
FSC® C154304