



### GENERAL DESCRIPTION

Valspar® Pro-Hide® Gold Ultra Interior is a self-priming, premium quality professional latex coating offering good hide and coverage. A zero VOC formula, Valspar® Pro-Hide® Gold Ultra is also GREENGUARD Gold certified for indoor air quality, offering a limited warranty. Apply by spray, brush or roller for a smooth, uniform finish. Valspar® Pro-Hide® Gold Ultra also offers excellent touchup properties along with easy cleanup with soap & water.

#### Product Features:

- Good hide & coverage
- Smooth, uniform finish
- Good durability
- Excellent touch-up
- Zero VOC formula
- GREENGUARD Gold certified for low chemical emissions
- Easy cleanup

### WHERE TO USE

Properly prepared interior walls and ceilings.

### SHIPPING AND PACKAGING

#### Freight Classification:

Paint or paint related material. Protect from freezing.

#### Packaging:

Gallon – 4 per carton  
5 gallon

### COMPOSITION

#### Base and Fill Levels

(oz./gal.)

White	128
Pastel	124
Tint Base	120
Clear Base	116

### APPLICATION

Stir paint thoroughly. Intermix containers for uniformity. Apply product when surface, air and product temperatures are between 50-90°F. Apply with a premium-quality brush, a synthetic roller cover or airless spray (2000 PSI, .015"-.019" tip). Thinning not required. Some deep or bright colors, surface conditions and application techniques may impact coverage and require multiple coats to achieve your optimal coverage. For additional application tips go to Valspar.com.

#### Airless Spray:

**Pressure:** 2000 PSI

**Tip:** 0.015–0.019"

**Brush:** Premium-quality brush

**Roller:** Premium-quality synthetic roller

### CLEANUP/STORAGE/

### DISPOSAL

Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

### PRODUCT SPECIFICATIONS

- o **Vehicle Type:** Acrylic
- o **Viscosity:** 105-111 Krebs Units
- o **Gloss:** 40–50 Units @ 85° angle
- o **Flashpoint:** N/A
- o **VOC (g/L):** < 50 g/L – 0.42 lb/gal as per 40 CFR 59.406
- o **Volume Solids:** 39%
- o **Weight Solids:** 52%
- o **Weight Per Gallon:** 10.63 lbs./gal.
- o **Practical Coverage:** Covers approximately 300–400 sq. ft. per gallon (27–37 m<sup>2</sup> per 3.78 L) depending on surface porosity. Do not thin.
- o **Recommended Film Thickness:** 4.0 mil Wet  
1.5 mil Dry
- o **Dry Time @ 77 °F and 50% Relative Humidity**
  - ▯ **To The Touch:** 1 hour
  - ▯ **Recoat:** 4 hours
- o **Application Temperature:** 50–90 °F (10–32 °C)
- o **Storage Temperature:** 40–90 °F (5–32 °C)



# Valspar® Pro-Hide Gold® Ultra Interior Semi-Gloss Latex Paint

---

## Series 6400

### SURFACE PREPARATION

Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Scrape and sand peeled or damaged paint. Sand glossy surfaces dull. Priming: This product can be used to prime patched areas, unpainted surfaces and lightly stained areas before applying it as the finish coat. For best results on heavily stained areas, use a coat of an appropriate stain-blocking primer. For drastic color changes or deep, vivid colors, prime with this product or an appropriate tintable primer for your optimal color accuracy and coverage.

### LIMITED WARRANTY

This product is warranted to meet the application, appearance, and performance properties stated on the label. This warranty covers product that is applied to a properly prepared surface in accordance with label directions and excludes failure due to deterioration of the underlying surface, structural defects or failure of previous paint. If the product fails to perform as warranted, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal or lesser value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state. CONTRACTOR AND COMMERCIAL CUSTOMERS: When used for commercial or nonresidential applications, this product is warranted to perform as indicated on the product label and to be free of material defects. At its option, Valspar will replace or refund the original purchase price of this product if it does not perform as labeled or is proven to be defective. All other warranty terms above apply. Valsparpaint.com/1-877-VALSPAR.

### LEAD WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### CAUTIONS

**White, Pastel, Tint, Base:** Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN

**Clear Base:** Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN

**EMERGENCY MEDICAL TELEPHONE: 1-888-345-5732**

Valspar, Cleveland, Ohio 44115  
1-877-VALSPAR (825-7727)  
[valsparpaint.com](http://valsparpaint.com)  
Revised: 9/21/22  
Version: 6400SG