



Valspar® Pro-Hide Gold® Ultra Exterior Flat Latex Paint

Series 6500

GENERAL DESCRIPTION

Valspar® Pro-Hide® Gold Ultra Exterior is a 100% acrylic formula that provides excellent durability, and outstanding hide and coverage. It can be applied to a variety of exterior surfaces at temperatures as low as 35°F, and is mildew-resistant. Great touch-up and flow & leveling qualities allow for a smooth, uniform finish while applying with spray, brush or roller.

Product Features:

- Good adhesion
- Resists fading
- Smooth, uniform finish
- Good hide & coverage
- 35°F low temperature application
- Provides a mildew-resistant finish
- Easy cleanup

WHERE TO USE

Properly prepared exterior surfaces of wood, hardboard, aluminum siding, vinyl siding, masonry, brick, stucco, cement composition panels and metal. Not for use on floors.

SHIPPING AND PACKAGING

Freight Classification:

Paint or paint related material. Protect from freezing.

Packaging:

Gallon – 4 per carton
5 gallon

COMPOSITION

Base and Fill Levels

(oz./gal.)

White	128
Pastel	124
Clear Base	116

APPLICATION

Stir paint thoroughly. Intermix containers to ensure uniform color. Apply only when paint, surface and air temperatures are 35-90°F (2-32°C) during application and drying time. Do not paint if temperatures are expected to be below 35°F (2°C) within 48 hours of application or when heavy dew or precipitation is expected in the next 2.5 hours. Brush: Use a premium-quality synthetic brush. Roller: 3/8-1/2 inch nap, premium-quality synthetic cover. Airless Spray: 2000 PSI, 0.015-0.021" tip. These recommendations are a starting point only. Due to variability in sprayers, we recommend testing your spray pattern and flow before proceeding. If spraying large surfaces, be sure to back-brush or roll immediately after spraying.

Airless Spray:

Pressure: 2000 PSI

Tip: 0.015–0.021"

Brush: Premium-quality synthetic brush

Roller: Premium-quality synthetic roller 3/8-1/2inch nap

CLEANUP/STORAGE/

DISPOSAL

Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

PRODUCT SPECIFICATIONS

- **Vehicle Type:** Acrylic
- **Viscosity:** 92-100 Krebs Units
- **Sheen:** 0–3 Units @ 85° angle
- **Flashpoint:** N/A
- **VOC:** < 50 g/L – 0.42 lb/gal as per 40 CFR 59.406
- **Volume Solids:** 31%
- **Weight Solids:** 46%
- **Weight Per Gallon:** 10.9 lbs./gal.
- **Practical Coverage:** Covers approximately 300–400 sq. ft. per gallon (27–37 m² per 3.78 L) depending on surface porosity. Do not thin.
- **Recommended Film Thickness:** 4.0 mil Wet
1.2 mil Dry
- **Dry Time @ 77 °F and 50% Relative Humidity**
 - **To The Touch:** 1 hour
 - **Recoat:** 4 hours
- **Dry Time @ 35–45 °F and 50% Relative Humidity**
 - **To The Touch:** 2 hours
 - **Recoat:** 24 hours
- **Application Temperature:** 35–90 °F (5–32°C)



Valspar® Pro-Hide Gold® Ultra Exterior Flat Latex Paint

Series 6500

SURFACE PREPARATION

Remove surface contaminants with an appropriate cleaner, rinse thoroughly and allow to dry. Remove peeled or damaged paint. Sand glossy surfaces dull. Seal stains with the appropriate primer. Caulk around windows, doors and other openings after spot priming bare surfaces. Knots and some woods, such as redwood and cedar, contain a high amount of tannin, a colored wood extract. If applied to these unpainted woods, the first coat of paint may show some staining, but it will be trapped in the first coat. A second coat will uniform the appearance. If staining persists, spot prime severe areas with a stain-blocking primer. Previously Painted: Spot prime bare areas, allow to dry and paint entire surface. Unpainted: Prime the surface with this product before applying the finish coat. Some specific surfaces require specialized treatment. Vinyl Siding: Repaint vinyl siding with a color similar to the original color to avoid excess heat absorption and to prevent buckling or warping. Concrete, Stucco, Masonry, Block, Cement Composition Siding: All new surfaces must be cured. Remove all form release and curing agents. If the pH is higher than 8, prime with a masonry primer. Rough surfaces may be smoothed with block filler. Cracks, voids and other holes should be repaired with an elastomeric patch or sealant. For drastic color changes or deep, vivid colors, prime with this product or an appropriate tintable primer for your optimal color accuracy and coverage..

LEAD WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

LIMITED WARRANTY

This product is warranted to meet the application, appearance, and performance properties stated on the label. This warranty covers product that is applied to a properly prepared surface in accordance with label directions and excludes failure due to deterioration of the underlying surface, structural defects or failure of previous paint. If the product fails to perform as warranted, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal or lesser value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state. CONTRACTOR AND COMMERCIAL CUSTOMERS: When used for commercial or nonresidential applications, this product is warranted to perform as indicated on the product label and to be free of material defects. At its option, Valspar will replace or refund the original purchase price of this product if it does not perform as labeled or is proven to be defective. All other warranty terms above apply. Valsparpaint.com/1-877-VALSPAR.

CAUTIONS

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN

EMERGENCY MEDICAL TELEPHONE: 1-888-345-5732

Valspar, Cleveland, Ohio 44115
1-877-VALSPAR (825-7727)
valsparpaint.com
Revised: 9/21/22
Version: 6500F