



### GENERAL DESCRIPTION

Valspar® Skylight® Color-Changing Ceiling Paint is a quality latex paint intended for pre-primed ceilings or previously painted ceilings. Never miss a spot as Valspar Skylight Color-Changing Ceiling Paint goes on purple but dries white! Offering a flat finish, there is no glossy glare as the paint easily conceals flaws. Spatter-resistant so cleanup is easy. GREENGUARD Gold certified for indoor air quality.

#### Product Features:

- Goes on purple, dries white
- Spatter resistant
- Dries to a smooth finish
- GREENGUARD Gold certified for low chemical emissions
- Easy cleanup

### SHIPPING AND PACKAGING

#### Freight Classification:

Paint or paint related material. Protect from freezing.

#### Packaging:

Gallon – 4 per carton

### COMPOSITION

#### Base and Fill Levels

(oz./gal.)

White

128

### APPLICATION

Stir paint thoroughly. Intermix containers for uniformity. Apply product when surface, air and product temperatures are between 50-90°F. Apply with a premium-quality brush, a synthetic roller cover or airless spray (2000 PSI, .017"-.021" tip). Thinning not required. Certain deep or bright colors may require an additional coat for complete hide. Surface conditions and application technique may impact coverage..

#### Airless Spray:

**Pressure:** 2000 PSI

**Tip:** 0.017–0.021"

**Brush:** Premium-quality

**Roller:** Premium-quality roller

### CLEANUP/STORAGE/

### DISPOSAL

Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

### WHERE TO USE

Properly prepared durable textured or plain interior ceilings including previously painted and primed plaster, drywall and acoustical tile. See Surface preparation for "blown on" soft-fibered ceiling surfaces.

### PRODUCT SPECIFICATIONS

- **Vehicle Type:** Vinyl Acrylic
- **Viscosity:** 95-105 Krebs Units
- **Sheen:** 0-5 units at 85°
- **Flashpoint:** N/A
- **VOC (g/L):** < 50 g/L 0.42 lb./gal as per 40 CFR 59.406
- **Weight Per Gallon:** 11.02 lb/gal
- **Volume Solids:** 33.7%
- **Weight Solids:** 49.6%
- **Practical Coverage:** Covers approximately 400 sq. ft. per gallon (37 m<sup>2</sup> per 3.78 L) depending on surface porosity. Significantly less on acoustical tile.
- **Recommended Film Thickness:** 4.0 mils wet, 1.35 mils dry
- **Dry Time @ 77 °F and 50% Relative Humidity**  
**To Touch:** 30-60 min  
**Recoat:** 2-4 hours
- **Application Temperature:** 50–90 °F (10–32 °C)
- **Storage Temperature:** 40–90 °F (5–32 °C)



# Valspar® Skylight® Color-Changing Ceiling Paint

---

## Series 15028

### **SURFACE PREPARATION**

Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Patch cracks and spot prime. Remove gloss from shiny surfaces. Acoustical tile: Vacuum or dust tiles to remove embedded dust. To maintain the sound absorbing qualities of the tile, do not use a primer. Apply ceiling paint directly to the tiles. Test vinyl-coated tiles to ensure adhesion. Do not attempt to fill or clog acoustical perforations. "Blown-on" soft-fibred ceilings: Caution! All water-based paints will loosen or deteriorate a "blown-on" soft-fibred ceiling surface and make for a difficult repair. If you are not sure about your ceiling texture type, apply a small test area in a closet or other hidden spot. If deterioration occurs and if painting is necessary, priming with an oil-based primer may help minimize the deterioration. Do not use a latex primer.

### **LIFETIME LIMITED**

#### **WARRANTY**

If this product, when applied according to product application instructions to a properly prepared interior surface, fails to perform to your complete satisfaction for as long as you own your home, Valspar shall, upon presentation of proof of purchase to the store where the product was purchased, either replace an equivalent quantity of product free of charge or refund the original purchase price. This warranty shall not apply to any defect or damage resulting from improper surface preparation, structural defects, failure of a previous paint or improper application of the product. This is your sole remedy under this warranty. This warranty is made to the original residential consumer paint purchaser and is not transferable. THIS WARRANTY EXCLUDES (1) LABOR OR COSTS ASSOCIATED WITH LABOR FOR THE APPLICATION OR REMOVAL OF ANY PRODUCT, AND (2) ANY INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state. Valsparpaint.com /1-877-VALSPAR.

### **LEAD WARNING**

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### **CAUTIONS**

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

**EMERGENCY MEDICAL TELEPHONE: 1-888-345-5732**

Valspar, Cleveland, Ohio 44115  
1-877-VALSPAR (825-7727)  
valsparpaint.com  
Revised: 9/21/22  
Version: 15028