



VARATHANE® FILL STICKS

DESCRIPTION AND USES

Varathane® Fill Sticks are a quick and easy way to repair scratches, nicks, dents or other minor imperfections in any wood surface. They are suitable for touching up furniture, cabinets, trim, doors and floors. Varathane Fill Sticks can be used to complement Varathane Premium Wood Stains or you can blend different Fill Sticks to create custom colors.

PRODUCTS

6 Pack Case	4 Pack Case	DESCRIPTION
215362	398982	Color Group 1
215363	398893	Color Group 2
215364	---	Color Group 3
215365	398984	Color Group 4
215366	---	Color Group 5
215367	398985	Color Group 6
215368	---	Color Group 7
215369	398986	Color Group 8
215370	398987	Color Group 9
215371	398988	Color Group 10
266909	398990	Color Group 11
359932	398989	Color Group 12

PRODUCT APPLICATION

SURFACE PREPARATION

If the area around the nick or dent is rough, sand the area smooth by sanding with #120 grit sandpaper in the direction of the grain. Remove all sanding dust with a vacuum or clean rag dampened with mineral spirits.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)

APPLICATION

Prior to repairs, determine the Fill Stick color that best matches the wood project. See the front panel of the package for Fill Stick color identification. Test the Fill Stick in an inconspicuous area to ensure the chosen color will match the project. Work the Fill Stick into the defect until filled. Remove excess material using a plastic putty knife.

PROTECTING YOUR PROJECT

If desired, additional protection of the repaired area can be achieved by applying a thin coat of Varathane Polyurethane. Apply the polyurethane with an artist acrylic paint brush and follow the manufacturer's directions for dry times.

	TECHNICAL DATA	VAR-25
	VARATHANE® FILL STICKS	

PHYSICAL PROPERTIES

		FILL STICKS
Resin Type		Waxes
Pigment Type		Inorganic and Organic
Solvents		None
Weight	Per Gallon	8.75 lbs.
	Per Liter	1.05 kg
Solids	By Weight	100%
	By Volume	100%
Volatile Organic Compounds		None
Practical Coverage		Varies with wood type
Shelf Life		3 years
Flash Point		NA
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.